### **NORMA**

# CE UK IKO5 IP65

## An Elegant and Sturdy Bollard






With its square frame, matching column options, and four-way light distribution NORMA bollard is a reliable choice for pathways, landscaped areas, and other public spaces.

- Minimized glare with hidden light source
- Four-way light distribution to illuminate areas and pathways while adding a unique effect
- Different height options and matching column to complement high-end architectural projects
- Minimalistic design to blend in with different types of architecture
- Easy installation and maintenance

Product code	Product name	Light distribution	Delivered lumens flux	Rated input power	Colour temperature	Control	Weight
LB6054.693-EN	NORMA S	[SYM-4L] 120°,	199 - 432 lm	6.5 - 10 W	2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 70, 4000 K CRI 80	On/Off, DALI	3.5 kg







**[SYM-4L]**Symmetric,
Special effect: 4
lines

#### **Extras**

Consult the factory

Luminaire body options

120-277V 50/60Hz

DPC

**UNI** 120-277V 50/60Hz **DPC**Double powder coating

# Accessories (To be ordered separately)

### Anchorages



**6281001** 6281001







[HM2] Dark grey



[HM3] Anthracite grey



[HM4] Light grey



[HM5] White



[HM6] Bronze



[CC]
Custom
colour
(Please
specify RAL
code)