

## VLORA

Reliable and Sturdy Light Column  
Family


CE UK CA IK07 IP65



With its plain look and low glare optics, VLORA is a reliable choice for exterior site lighting applications.

- Reduced glare with indirect illumination
- Optimized light distribution with secondary reflector technology
- A lens and a reflector combined to provide increased optical efficiency (HYB)
- Uniform lighting distribution through multifaceted reflectors
- Simple design that blends in with different types of architecture

Product code	Product name	Light distribution	Delivered lumens flux	Rated input power	Colour temperature	Control	Weight
LB6058.694-EN	VLORA	[SYM] 98°,	1550 - 3269 lm	26 - 40 W	2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 70, 4000 K CRI 80	On/Off, DALI	19.87 kg (3 m), 23.61 kg (4 m)



[SYM]

Symmetric

## Extras

Consult the factory

120-277V  
50/60Hz

UNI

120-277V 50/60Hz

Luminaire body options


DPC

DPC

Double powder  
coating


## Accessories (To be ordered separately)

Optical accessories




**Hat for VLORA**  
100817064

Anchorage




**90CJ004**  
90CJ004

Flanges




**F0603B**  
F0603B


Flange covers




**C1F2C**  
C1F2C




[HM1]  
Black




[HM2]  
Dark grey




[HM3]  
Anthracite  
grey



[HM4]  
Light grey



[HM5]  
White



[HM6]  
Bronze



[CC]  
Custom  
colour  
(Please  
specify RAL  
code)