

VLORA

Reliable and Sturdy Light Column
Family

CE UK CA IK07 IP65




PHASED-
OUT

With its plain look and low glare optics, VLORA is a reliable choice for exterior site lighting applications.

- Reduced glare with indirect illumination
- Optimized light distribution with secondary reflector technology
- A lens and a reflector combined to provide increased optical efficiency (HYB)
- Uniform lighting distribution through multifaceted reflectors
- Simple design that blends in with different types of architecture

Product code	Product name	Light distribution	Delivered lumens flux	Rated input power	Colour temperature	Control	Weight
LB6058.694-EN	VLORA	[SYM] 98°,	1550 - 3269 lm	26 - 40 W	2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 70, 4000 K CRI 80	On/Off, DALI	19.87 kg (3 m), 23.61 kg (4 m)



[SYM]

Symmetric

Extras

Consult the factory

120-277V
50/60Hz

UNI

120-277V 50/60Hz

Luminaire body options


DPC

DPC

Double powder
coating


Accessories (To be ordered separately)

Optical accessories




Hat for VLORA
100817064

Anchorage




90CJ004
90CJ004

Flanges




F0603B
F0603B


Flange covers




C1F2C
C1F2C




[HM1]
Black




[HM2]
Dark grey




[HM3]
Anthracite
grey



[HM4]
Light grey



[HM5]
White



[HM6]
Bronze



[CC]
Custom
colour
(Please
specify RAL
code)