

## VLORA

Reliable and Sturdy Light Column  
Family

CE UK CA IK07 IP65





With its plain look and low glare optics, VLORA is a reliable choice for exterior site lighting applications.

- Equipped with high-efficiency and long-lasting LED light source
- Efficient LED technology with high transmittance lenses
- Minimized stray light with specially made UV-stable diffuser
- Simple design that blends in with different types of architecture
- Easy installation and maintenance

Product code	Product name	Light distribution	Delivered lumens flux	Rated input power	Colour temperature	Control	Weight
LL6058.550-EN	VLORA	[SYM] 108,	1731 - 3038 lm	23 - 34 W	2200 K CRI 80, 2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 70	On/Off, DALI, AutoDIM, StepDIM	19.87 kg (3 m), 23.61 kg (4 m)

LB6058.694



[SYM]  
Symmetric

## Extras

External surge  
protection




**SP10**  
10 kV

Light output



**CLO**  
Constant light output

Consult the factory



**C2**  
Class II

Luminaire body options



**DPC**  
Double powder  
coating


## Accessories (To be ordered separately)

Optical accessories




**Hat for VLORA**  
100817064

Anchorage



**90CJ004**  
90CJ004

Flanges




**F0603B**  
F0603B

Flange covers

**HPR Pazarlama A.Ş.**  
Başkent OSB 22. Cd. No: 2, Malıköy, Temelli,  
Sincan, 06909 Ankara, Turkey  
+90 312 267 54 30  
info@hepergroup.com


**HEPER Europe GmbH**  
Ahornweg 5a, 58675  
Hemer, Germany  
+49 237 2901 2975  
infoEU@hepergroup.com

We reserve the right to change specifications  
without prior written notice. Edition: 13.05.2024.  
For current version visit [heperlighting.com](http://heperlighting.com). All  
flux (±%7 tolerance) and power values (±%10  
tolerance) are derived following appropriate IES,  
CIE, and applicable standards.




## C1F2C


C1F2C



**[HM1]**  
Black




**[HM2]**  
Dark grey




**[HM3]**  
Anthracite  
grey



**[HM4]**  
Light grey



**[HM5]**  
White



**[HM6]**  
Bronze



**[CC]**  
Custom  
colour  
(Please  
specify RAL  
code)