


VLORA

Reliable and Sturdy Light Column
Family



CE UK CA IK07 IP65 



With its plain look and low glare optics, VLORA is a reliable choice for exterior site lighting applications.

- Equipped with high-efficiency and long-lasting LED light source
- Efficient LED technology with high transmittance lenses
- Minimized stray light with specially made UV-stable diffuser
- Simple design that blends in with different types of architecture
- Easy installation and maintenance

Product code	Product name	Light distribution	Delivered lumens flux	Rated input power	Colour temperature	Control	Weight
LL6058.550-EN	VLORA	[SYM] 108,	1731 - 3038 lm	23 - 34 W	2200 K CRI 80, 2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 70	On/Off, DALI, AutoDIM, StepDIM	19.87 kg (3 m), 23.61 kg (4 m)



[SYM]
Symmetric

Extras

External surge protection




SP10
10 kV

Light output



CLO
Constant light output

Consult the factory



C2
Class II

Luminaire body options



DPC
Double powder coating


Accessories (To be ordered separately)

Optical accessories




Hat for VLORA
100817064

Anchorage




90CJ004
90CJ004

Flanges




F0603B
F0603B


Flange covers




C1F2C
C1F2C



[HM1]
Black




[HM2]
Dark grey




[HM3]
Anthracite
grey



[HM4]
Light grey



[HM5]
White



[HM6]
Bronze



[CC]
Custom
colour
(Please
specify RAL
code)