
## VLORA








## With its plain look and low glare optics, VLORA is a reliable choice for exterior site lighting applications.

- Equipped with high-efficiency and long-lasting LED light source
- Efficient LED technology with high transmittance lenses
- Minimized stray light with specially made UV-stable diffuser
- Simple design that blends in with different types of architecture
- Easy installation and maintenance

Product code	Product name	Light distribution	Delivered lumens flux	Rated input power	Color temperature	Control	Weight
LB6058.694-US	VLORA	[SYM] 98°,	1550 - 3269 lm	26 - 40 W	2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 70, 4000 K CRI 80	On/Off, 0-10V	43.7 lbs (10'), 51.9 lbs (13')







**[SYM]** Symmetric

Extras

Luminaire body options



DPC Double powder coating

## Accessories (Included)

## Base platesBolt coversOptical accessoriesAnchor boltsImage: Delta coversImage: Delta covers

HEPER USA LLC W227 N546 Westmound Drive Waukesha, 53186 Wisconsin, United States +1 312 910 9740 infoUS@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 05.05.2024. For current version visit heperlighting.com. All flux ( $\pm$ %7 tolerance) and power values ( $\pm$ %10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

Accessories (To be ordered separately)

2/3

|--|

[HM4]

Light gray

[HM5]

White

[HM6]

Bronze

[HM1]

Black

[HM2]

Dark gray

[HM3]

Anthracite

gray

[CC] Custom color (Please specify RAL code)

HEPER USA LLC W227 N546 Westmound Drive Waukesha, 53186 Wisconsin, United States +1 312 910 9740 infoUS@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 05.05.2024. For current version visit heperlighting.com. All flux ( $\pm$ %7 tolerance) and power values ( $\pm$ %10 tolerance) are derived following appropriate IES, CIE, and applicable standards.