## ELIPSO

A reliable floodlight





PHASED-OUT

## ELIPSO, with variety of optics, is an upstanding floodlight for various applications.

- Photobiological safety: Risk group 1

|  | Product code  | Product name | Light<br>distribution | Delivered<br>lumens flux | Rated input<br>power | Color temperature            | Control | Weight   |
|--|---------------|--------------|-----------------------|--------------------------|----------------------|------------------------------|---------|----------|
|  | LF8008.504-US | ELIPSO       |                       | 500 - 600 lm             | 11 W                 | 3000 K CRI 80, 4000 K CRI 70 | On/Off  | 6.94 lbs |

| [HM1] | [HM2] | [HM3] | [HM4] | [HM5] | [HM6] | [CC] |
|-------|-------|-------|-------|-------|-------|------|
|       |       |       |       |       |       |      |

Light gray

White

Bronze

Dark gray

Black

Anthracite

gray

[CC] Custom color (Please specify RAL code)

HEPER USA LLC W227 N546 Westmound Drive Waukesha, 53186 Wisconsin, United States +1 312 910 9740 infoUS@hepergroup.com

We reserve the right to change specifications without prior written notice. Edition: 18.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.