

## KREIS

Highly Practical, Elegant, Aesthetic  
Post-top Family with Modern Design



IK08 IP66




With the combination of long-life and maximum efficiency optics coming into play with a modern aesthetic structure and strong engineering fundamentals, KREIS becomes obscure yet still supports the illumination tasks for modern cities and other open spaces.


- Equipped with high-efficiency and long-lasting LED light source
- Superior glare management with diffused glass
- Uniform light distribution with high level of operating efficiency
- Optimized thermal design resulting in longer life cycle
- Modern and elegant design creating a unique touch in exterior applications

Product code	Product name	Light distribution	Delivered lumens flux	Rated input power	Colour temperature	Control	Weight
LL2031.511-EN	KREIS	[SYM] 100°,	5287 - 5737 lm	60 W	2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 70, 4000 K CRI 80	On/Off, DALI, AutoDIM, StepDIM	5.33 kg
LL2039.517-EN	KREIS C	[SYM] 97x102°,	3465 - 4046 lm	40 W	2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 70, 4000 K CRI 80	On/Off, DALI, AutoDIM, StepDIM	4.3 kg

LL2031.511



LL2039.517

**[SYM]**

Symmetric

## Extras


External surge protection

**SP10**  
10 kV

Light output

**CLO****CLO**  
Constant light output







Consult the factory

**C2**  
Class II

Consult the factory

120-277V  
50/60Hz**UNI**  
120-277V 50/60Hz

Luminaire body options

**DPC****DPC**  
Double powder coating**[HM1]**  
Black**[HM2]**  
Dark grey**[HM3]**  
Anthracite grey**[HM4]**  
Light grey**[HM5]**  
White**[HM6]**  
Bronze**[CC]**  
Custom colour  
(Please specify RAL code)