

[SYM-3L]

Symmetric, Special
effect: 3 lines -
38x117°

Configurations

Light distribution	[SYM-3L] 38x117°
Delivered lumens flux	872 - 1900 lm
Rated input power	15 - 29 W
Color temperature	2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 70, 4000 K CRI 80
Lifetime L90 (hour)	>72, 600
Lifetime L80 (hour)	>72, 600

Options

Control	On/Off, 0-10V
Product colors	

Extras


Luminaire body options	Double powder coating
-------------------------------	-----------------------

Technical information

Housing	Corrosion resistant, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Liquid silicone
Lens / Reflector	PMMA lens with high optical efficiency
Glass / Diffusor	Tempered safety glass
Impact protection	IK05
Ingress protection	IP65
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Weight	68 lbs
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	6/6 kV
Power factor	> 0.95
Through wiring	Single power cord entry
Operating temperature	-40...50°C


Accessories (To be ordered separately)

Anchor bolts










90CJ001
90CJ001

Bolt covers



C1J2K
C1J2K

Project name				Type		Quantity	
Date		Note					
LB6052.509-US- ____-____-____-____-____-____-____							

Light distribution	Rated input power	Color temperature	Control	Product colors
[SYM-3L] Symmetric, Special effect: 3 lines - 38x117°	[350] 15 W [700] 29 W	[827] 2700 K CRI 80 [830] 3000 K CRI 80 [740] 4000 K CRI 70 [840] 4000 K CRI 80	[ONOFF] On/Off [0-10V] 0-10V	[HM1]  Black [HM2]  Dark gray [HM3]  Anthracite gray [HM4]  Light gray [HM5]  White [HM6]  Bronze [CC]  Custom color (Please specify RAL code)
Extras	Accessories (<i>To be ordered separately</i>)			
Luminaire body options	Anchor bolts			
	[90CJ001] 90CJ001			
	Bolt covers			
	[C1J2K] C1J2K			
[DPC] Double powder coating				

Configuration code	Light distribution	Delivered lumens flux	Rated input power	Color temperature	Control
LB6052.509-US-SYM-3L-350-740	[SYM-3L] Symmetric, Special effect: 3 lines - 38x117°	1084 lm	15 W	4000 K CRI 70	On/Off, 0-10V
LB6052.509-US-SYM-3L-350-827	[SYM-3L] Symmetric, Special effect: 3 lines - 38x117°	872 lm	15 W	2700 K CRI 80	On/Off, 0-10V
LB6052.509-US-SYM-3L-350-830	[SYM-3L] Symmetric, Special effect: 3 lines - 38x117°	888 lm	15 W	3000 K CRI 80	On/Off, 0-10V
LB6052.509-US-SYM-3L-350-840	[SYM-3L] Symmetric, Special effect: 3 lines - 38x117°	985 lm	15 W	4000 K CRI 80	On/Off, 0-10V
LB6052.509-US-SYM-3L-700-740	[SYM-3L] Symmetric, Special effect: 3 lines - 38x117°	1900 lm	29 W	4000 K CRI 70	On/Off, 0-10V
LB6052.509-US-SYM-3L-700-827	[SYM-3L] Symmetric, Special effect: 3 lines - 38x117°	1514 lm	29 W	2700 K CRI 80	On/Off, 0-10V
LB6052.509-US-SYM-3L-700-830	[SYM-3L] Symmetric, Special effect: 3 lines - 38x117°	1531 lm	29 W	3000 K CRI 80	On/Off, 0-10V
LB6052.509-US-SYM-3L-700-840	[SYM-3L] Symmetric, Special effect: 3 lines - 38x117°	1718 lm	29 W	4000 K CRI 80	On/Off, 0-10V