

VLORA


LB6058.694-US



Ø450 mm
Ø17 23/32"

462 mm
18 3/16"

Ø150mm
Ø5 29/32"



H
3000 mm 10'
4000 mm 13'




[SYM]
Symmetric - 98°

Configurations

Light distribution	[SYM] 98°
Delivered lumens flux	1550 - 3269 lm
Rated input power	26 - 40 W
Color temperature	2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 70, 4000 K CRI 80
Lifetime L90 (hour)	>72, 600
Lifetime L80 (hour)	>72, 600

Options

Control	On/Off, 0-10V
Product colors	
Height	10', 13.1',

Extras


Luminaire body options	Double powder coating
------------------------	-----------------------

Technical information

Housing	Corrosion resistant, die-cast, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	High reflectance aluminium coating
Glass / Diffusor	Tempered safety glass
Impact protection	IK07
Ingress protection	IP65
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Weight	43.7 lbs (10'), 51.9 lbs (13')
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	6/6 kV
Power factor	> 0.95
Through wiring	Single power cord entry
Operating temperature	-40...50°C
Pole detail	Poles are supplied with flange plate. Flange cover and anchorage can be ordered separately. Embedded base is optional
Notes	Please contact the sales department regarding this product's availability.


Accessories (Included)

Base plates



F0603B
F0603B

Bolt covers



C1F2C
C1F2C


Accessories (To be ordered separately)

Optical accessories



Hat for VLORA
100817064








Anchor bolts



90CJ004
90CJ004

Project name				Type		Quantity	
Date		Note					

LB6058.694-US-____-____-____-____-____-____-____

Light distribution	Rated input power	Color temperature	Control	Product colors
[SYM] Symmetric - 98°	[700] 26 W [1050] 40 W	[827] 2700 K CRI 80 [830] 3000 K CRI 80 [740] 4000 K CRI 70 [840] 4000 K CRI 80	[ONOFF] On/Off [0-10V] 0-10V	[HM1]  Black [HM2]  Dark gray [HM3]  Anthracite gray [HM4]  Light gray [HM5]  White [HM6]  Bronze [CC]  Custom color (Please specify RAL code)
Height	Extras	Accessories (Included)	Accessories (<i>To be ordered separately</i>)	
[H3] 10' [H4] 13.1' [HC]	Luminaire body options	Base plates	Optical accessories	
	[DPC] Double powder coating	[F0603B] F0603B	[100817064] Hat for VLORA	
		Bolt covers	Anchor bolts	
		[C1F2C] C1F2C	[90CJ004] 90CJ004	

Configuration code	Light distribution	Delivered lumens flux	Rated input power	Color temperature	Control
LB6058.694-US-SYM-1050-740	[SYM] Symmetric - 98°	3269 lm	40 W	4000 K CRI 70	On/Off, 0-10V
LB6058.694-US-SYM-1050-827	[SYM] Symmetric - 98°	2654 lm	40 W	2700 K CRI 80	On/Off, 0-10V
LB6058.694-US-SYM-1050-830	[SYM] Symmetric - 98°	2430 lm	40 W	3000 K CRI 80	On/Off, 0-10V
LB6058.694-US-SYM-1050-840	[SYM] Symmetric - 98°	2700 lm	40 W	4000 K CRI 80	On/Off, 0-10V
LB6058.694-US-SYM-700-740	[SYM] Symmetric - 98°	1881 lm	26 W	4000 K CRI 70	On/Off, 0-10V
LB6058.694-US-SYM-700-827	[SYM] Symmetric - 98°	1550 lm	26 W	2700 K CRI 80	On/Off, 0-10V
LB6058.694-US-SYM-700-830	[SYM] Symmetric - 98°	1568 lm	26 W	3000 K CRI 80	On/Off, 0-10V
LB6058.694-US-SYM-700-840	[SYM] Symmetric - 98°	1760 lm	26 W	4000 K CRI 80	On/Off, 0-10V