



LIA

LB6059.599-US




[SYM-4L]

Symmetric, Special
effect: 4 lines - 50°

Configurations

Light distribution	[SYM-4L] 50°
Delivered lumens flux	256 - 582 lm
Rated input power	14 - 29 W
Color temperature	2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 70, 4000 K CRI 80
BUG rating	B0-U0-G1, B0-U0-G0
Lifetime L90 (hour)	>55, 000
Lifetime L80 (hour)	>55, 000

Options

Control	On/Off, 0-10V
Product colors	
Height	1.6',

Extras


Consult the factory	Custom pattern
Luminaire body options	Double powder coating

Technical information

Mounting	Surface mountable
Housing	Corrosion resistant, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	Glass lens with high optical efficiency
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP66
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Weight	15 lbs
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	10/6 kV
Power factor	> 0.95
Through wiring	Single power cord entry
Operating temperature	-40...50°C
Power cord	20" of outdoor use rated flexible power cord

Accessories (To be ordered separately)

Anchor bolts










628I003

628I003

Project name				Type		Quantity	
Date		Note					

LB6059.599-US- ____-____-____-____-____-____-____-____-____-____

Light distribution	Rated input power	Color temperature	Control	Product colors
[SYM-4L] Symmetric, Special effect: 4 lines - 50°	[350] 14 W [500] 21 W [700] 29 W	[827] 2700 K CRI 80 [830] 3000 K CRI 80 [740] 4000 K CRI 70 [840] 4000 K CRI 80	[ONOFF] On/Off [0-10V] 0-10V	[HM1]  Black [HM2]  Dark gray [HM3]  Anthracite gray [HM4]  Light gray [HM5]  White [HM6]  Bronze [CC]  Custom color (Please specify RAL code)
Height	Extras	Accessories (<i>To be ordered separately</i>)		
[H0.50] 1.6' [HC]	Consult the factory	Anchor bolts		
	[CP] Custom pattern	[628I003] 628I003		
	Luminaire body options			
	[DPC] Double powder coating			

Configuration code	Light distribution	Delivered lumens flux	Rated input power	Color temperature	Control
LB6059.599-US-SYM-4L-350-740	[SYM-4L] Symmetric, Special effect: 4 lines - 50°	290 lm	14 W	4000 K CRI 70	On/Off, 0-10V
LB6059.599-US-SYM-4L-350-827	[SYM-4L] Symmetric, Special effect: 4 lines - 50°	256 lm	14 W	2700 K CRI 80	On/Off, 0-10V
LB6059.599-US-SYM-4L-350-830	[SYM-4L] Symmetric, Special effect: 4 lines - 50°	267 lm	14 W	3000 K CRI 80	On/Off, 0-10V
LB6059.599-US-SYM-4L-350-840	[SYM-4L] Symmetric, Special effect: 4 lines - 50°	274 lm	14 W	4000 K CRI 80	On/Off, 0-10V
LB6059.599-US-SYM-4L-500-740	[SYM-4L] Symmetric, Special effect: 4 lines - 50°	415 lm	21 W	4000 K CRI 70	On/Off, 0-10V
LB6059.599-US-SYM-4L-500-827	[SYM-4L] Symmetric, Special effect: 4 lines - 50°	366 lm	21 W	2700 K CRI 80	On/Off, 0-10V
LB6059.599-US-SYM-4L-500-830	[SYM-4L] Symmetric, Special effect: 4 lines - 50°	381 lm	21 W	3000 K CRI 80	On/Off, 0-10V
LB6059.599-US-SYM-4L-500-840	[SYM-4L] Symmetric, Special effect: 4 lines - 50°	392 lm	21 W	4000 K CRI 80	On/Off, 0-10V
LB6059.599-US-SYM-4L-700-740	[SYM-4L] Symmetric, Special effect: 4 lines - 50°	582 lm	29 W	4000 K CRI 70	On/Off, 0-10V
LB6059.599-US-SYM-4L-700-827	[SYM-4L] Symmetric, Special effect: 4 lines - 50°	513 lm	29 W	2700 K CRI 80	On/Off, 0-10V
LB6059.599-US-SYM-4L-700-830	[SYM-4L] Symmetric, Special effect: 4 lines - 50°	535 lm	29 W	3000 K CRI 80	On/Off, 0-10V
LB6059.599-US-SYM-4L-700-840	[SYM-4L] Symmetric, Special effect: 4 lines - 50°	550 lm	29 W	4000 K CRI 80	On/Off, 0-10V