

**OTTO**



LD7039.002-EN

CE UK CA IK07 IP65 



PHASED-  
OUT

140 mm  
5 33/64"



[N]  
Narrow - 25°

**Variants**

<b>Light distribution</b>	[N] 25°
<b>Delivered lumens flux</b>	955 - 1021 lm
<b>Rated input power</b>	18.5 W
<b>Colour temperature</b>	3000 K CRI 90, 4000 K CRI 90
<b>BUG rating</b>	B1-U0-G0

**Options**

<b>Control</b>	On/Off
<b>Product colours</b>	








**Extras**

<b>Consult the factory</b>	120-277V 50/60Hz
----------------------------	------------------

**Technical information**

<b>Housing</b>	Corrosion resistant, marine grade aluminum housing
<b>Finishing</b>	Chromate conversion pretreatment followed by electrostatic powder coating
<b>Fasteners</b>	Stainless steel (AISI 304 / EN 1.4301 grade)
<b>Gasket</b>	Silicone
<b>Glass / Diffusor</b>	Tempered safety glass
<b>Impact protection</b>	IK07
<b>Ingress protection</b>	IP65
<b>Input voltage</b>	220-240V 50/60Hz
<b>Insulation class</b>	Class I
<b>Wind catching area (EPA)</b>	0.02 m <sup>2</sup>
<b>Weight</b>	0.73 kg
<b>Driver</b>	Internal LED driver
<b>Power factor</b>	> 0.80
<b>Through wiring</b>	Single cable entry
<b>Cable</b>	0.2 m of flexible cable
<b>Notes</b>	This product is supplied without a bulb as standard. The shown lighting distribution and performance are indicative but can change depending on the bulb. Please consult the factory for bulb options and availability.

Project name		Type		Quantity	
Date		Note			
<b>LD7039.002-EN-__-__-__-__-EN-C1-__-__</b>					

Light distribution	Rated input power	Colour temperature	Control	Product colours
<b>[N]</b> Narrow - 25°	<b>[I]</b> 18.5 W	<b>[930]</b> 3000 K CRI 90  <b>[940]</b> 4000 K CRI 90	<b>[ONOFF]</b> On/Off	<b>[HM1]</b>  Black  <b>[HM2]</b>  Dark grey  <b>[HM3]</b>  Anthracite grey  <b>[HM4]</b>  Light grey  <b>[HM5]</b>  White  <b>[HM6]</b>  Bronze  <b>[CC]</b>  Custom colour (Please specify RAL code)
<b>Extras</b>				
<b>Consult the factory</b>				
<b>[UNI]</b> 120-277V 50/60Hz				

Variant code	Light distribution	Delivered lumens flux	Rated input power	Colour temperature	Control
LD7039.002-EN-N-930	[N] Narrow - 25°	955 lm	18.5 W	3000 K CRI 90	
LD7039.002-EN-N-940	[N] Narrow - 25°	1021 lm	18.5 W	4000 K CRI 90	