


REGIO 4 Module

LF8032.524-US



PHASED-OUT

[-2]
- 26°



[EL]
Elliptical - 15x40°



[N]
Narrow - NEMA Type 2 - 22°



[MN]
Medium narrow - NEMA Type 3 - 30°



[M]
Medium - NEMA Type 4 - 50°



[W]
Wide - NEMA Type 6 - 111°

Configurations

Light distribution	[-2] 26°, [EL] 15x40°, [N] 22°, [MN] 30°, [M] 50°, [W] 111°
Delivered lumens flux	93487 - 132044 lm
Rated input power	916 W
Color temperature	2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 70, 4000 K CRI 80, 5700 K CRI 90
Lifetime L90 (hour)	>102, 000
Lifetime L80 (hour)	>102, 000

Options

Control

On/Off, 0-10V

Product colors



Extras

Luminaire body options

Double powder coating

Technical information

Mounting

Yoke mount

Tilt angle

+45°/-45°

Housing

Corrosion resistant, marine grade aluminum housing

Finishing

Chromate conversion pretreatment followed by electrostatic powder coating

Fasteners

Stainless steel (AISI 304 / EN 1.4301 grade)

Gasket

Silicone rubber

Lens / Reflector

PMMA lens with high optical efficiency

Glass / Diffusor

Tempered safety glass

Impact protection

IK08

Ingress protection

IP66

Input voltage

120-277V 50/60Hz

Insulation class

Class I

Weight

93.17 lbs

LED module

High power LEDs on metal-core PCB

Driver

External LED driver

Driver surge protection

10/10 kV

Power factor

> 0.99

Through wiring

Single power cord entry

Operating temperature

-40...50°C

Power cord

40" of flexible power cord

Notes

Please contact the sales department regarding this product's availability.

HEPER USA LLC

W227 N546 Westmound Drive Waukesha, 53186

Wisconsin, United States




+1 312 910 9740

infoUS@hepergroup.com

We reserve the right to change specifications without prior written notice. Edition: 03.07.2023. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

Project name		Type		Quantity	
Date		Note			

LF8032.524-US-____-____-____-____-____-____

Light distribution	Rated input power	Color temperature	Control	Product colors
<p>[-2] - 26°</p> <p>[EL] Elliptical - 15x40°</p> <p>[N] Narrow - NEMA Type 2 - 22°</p> <p>[MN] Medium narrow - NEMA Type 3 - 30°</p> <p>[M] Medium - NEMA Type 4 - 50°</p> <p>[W] Wide - NEMA Type 6 - 111°</p>	<p>[700] 916 W</p>	<p>[827] 2700 K CRI 80</p> <p>[830] 3000 K CRI 80</p> <p>[740] 4000 K CRI 70</p> <p>[840] 4000 K CRI 80</p> <p>[957] 5700 K CRI 90</p>	<p>[ONOFF] On/Off</p> <p>[0-10V] 0-10V</p>	<p>[HM3]  Anthracite gray</p> <p>[HM4]  Light gray</p> <p>[CC]  Custom color (Please specify RAL code)</p>
Extras				
Luminaire body options				
[DPC] Double powder coating				

Configuration code	Light distribution	Delivered lumens flux	Rated input power	Color temperature	Control
LF8032.524-US-N-700-740	[N] Narrow - NEMA Type 2 - 22°	132044 lm	916 W	4000 K CRI 70	On/Off, 0-10V
LF8032.524-US-N-700-827	[N] Narrow - NEMA Type 2 - 22°	111292 lm	916 W	2700 K CRI 80	On/Off, 0-10V
LF8032.524-US-N-700-830	[N] Narrow - NEMA Type 2 - 22°	111292 lm	916 W	3000 K CRI 80	On/Off, 0-10V
LF8032.524-US-N-700-840	[N] Narrow - NEMA Type 2 - 22°	111292 lm	916 W	4000 K CRI 80	On/Off, 0-10V
LF8032.524-US-N-700-957	[N] Narrow - NEMA Type 2 - 22°	111292 lm	916 W	5700 K CRI 90	On/Off, 0-10V
LF8032.524-US-MN-700-740	[MN] Medium narrow - NEMA Type 3 - 30°	121372 lm	916 W	4000 K CRI 70	On/Off, 0-10V
LF8032.524-US-MN-700-827	[MN] Medium narrow - NEMA Type 3 - 30°	102301 lm	916 W	2700 K CRI 80	On/Off, 0-10V
LF8032.524-US-MN-700-830	[MN] Medium narrow - NEMA Type 3 - 30°	102301 lm	916 W	3000 K CRI 80	On/Off, 0-10V
LF8032.524-US-MN-700-840	[MN] Medium narrow - NEMA Type 3 - 30°	102301 lm	916 W	4000 K CRI 80	On/Off, 0-10V
LF8032.524-US-MN-700-957	[MN] Medium narrow - NEMA Type 3 - 30°	102301 lm	916 W	5700 K CRI 90	On/Off, 0-10V
LF8032.524-US-M-700-740	[M] Medium - NEMA Type 4 - 50°	110915 lm	916 W	4000 K CRI 70	On/Off, 0-10V
LF8032.524-US-M-700-827	[M] Medium - NEMA Type 4 - 50°	93487 lm	916 W	2700 K CRI 80	On/Off, 0-10V
LF8032.524-US-M-700-830	[M] Medium - NEMA Type 4 - 50°	93487 lm	916 W	3000 K CRI 80	On/Off, 0-10V
LF8032.524-US-M-700-840	[M] Medium - NEMA Type 4 - 50°	93487 lm	916 W	4000 K CRI 80	On/Off, 0-10V
LF8032.524-US-M-700-957	[M] Medium - NEMA Type 4 - 50°	93487 lm	916 W	5700 K CRI 90	On/Off, 0-10V
LF8032.524-US-W-700-740	[W] Wide - NEMA Type 6 - 111°	119952 lm	916 W	4000 K CRI 70	On/Off, 0-10V
LF8032.524-US-W-700-827	[W] Wide - NEMA Type 6 - 111°	101101 lm	916 W	2700 K CRI 80	On/Off, 0-10V
LF8032.524-US-W-700-830	[W] Wide - NEMA Type 6 - 111°	101101 lm	916 W	3000 K CRI 80	On/Off, 0-10V
LF8032.524-US-W-700-840	[W] Wide - NEMA Type 6 - 111°	101101 lm	916 W	4000 K CRI 80	On/Off, 0-10V
LF8032.524-US-W-700-957	[W] Wide - NEMA Type 6 - 111°	101101 lm	916 W	5700 K CRI 90	On/Off, 0-10V
LF8032.524-US-EL-700-740	[EL] Elliptical - 15x40°	114156 lm	916 W	4000 K CRI 70	On/Off, 0-10V
LF8032.524-US-EL-700-827	[EL] Elliptical - 15x40°	96215 lm	916 W	3000 K CRI 80	On/Off, 0-10V
LF8032.524-US-EL-700-830	[EL] Elliptical - 15x40°	96215 lm	916 W	2700 K CRI 80	On/Off, 0-10V
LF8032.524-US-EL-700-840	[EL] Elliptical - 15x40°	96215 lm	916 W	4000 K CRI 80	On/Off, 0-10V
LF8032.524-US-EL-700-957	[EL] Elliptical - 15x40°	96215 lm	916 W	5700 K CRI 90	On/Off, 0-10V
LF8032.524-US-N2-700-740	□ - 26°	127568 lm	916 W	4000 K CRI 70	On/Off, 0-10V
LF8032.524-US-N2-700-827	□ - 26°	107520 lm	916 W	2700 K CRI 80	On/Off, 0-10V
LF8032.524-US-N2-700-830	□ - 26°	107520 lm	916 W	3000 K CRI 80	On/Off, 0-10V
LF8032.524-US-N2-700-840	□ - 26°	107520 lm	916 W	4000 K CRI 80	On/Off, 0-10V
LF8032.524-US-N2-700-957	□ - 26°	107520 lm	916 W	5700 K CRI 90	On/Off, 0-10V