


REGIO A 6 Module

LF8032.536-US



PHASED-
OUT




[SLFB]

Special linear,
Forward throw -
106x28°

Configurations

Light distribution	[SLFB] 106x28°
Delivered lumens flux	72975 - 88870 lm
Rated input power	945 W
Color temperature	2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 70, 4000 K CRI 80
Lifetime L90 (hour)	>60,000
Lifetime L80 (hour)	>60,000

Options

Control	On/Off, 0-10V
Product colors	  




Extras

Luminaire body options	Double powder coating
------------------------	-----------------------

Technical information

Mounting	Yoke mount
Tilt angle	+45°/-45°
Housing	Corrosion resistant, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone rubber
Lens / Reflector	PMMA lens with high optical efficiency
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP66
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Wind catching area (EPA)	0.12 m²
Weight	129.60 lbs
LED module	High power LEDs on metal-core PCB
Driver	External LED driver
Driver surge protection	10/10 kV
Power factor	> 0.99
Through wiring	Single power cord entry
Operating temperature	-40...50°C
Power cord	40" of flexible power cord
Notes	Please contact the sales department regarding this product's availability.

Project name				Type		Quantity	
Date		Note					
LF8032.536-US- ____-____-____-____-____-____-____							

Light distribution	Rated input power	Color temperature	Control	Product colors
[SLFB] Special linear, Forward throw - 106x28°	[700] 945 W	[827] 2700 K CRI 80 [830] 3000 K CRI 80 [740] 4000 K CRI 70 [840] 4000 K CRI 80	[ONOFF] On/Off [0-10V] 0-10V	[HM3]  Anthracite gray [HM4]  Light gray [CC]  Custom color (Please specify RAL code)
Extras				
Luminaire body options				
[DPC] Double powder coating				

Configuration code	Light distribution	Delivered lumens flux	Rated input power	Color temperature	Control
LF8032.536-US-SLFB-700-740	[SLFB] Special linear, Forward throw - 106x28°	88870 lm	945 W	4000 K CRI 70	On/Off, 0-10V
LF8032.536-US-SLFB-700-827	[SLFB] Special linear, Forward throw - 106x28°	72975 lm	945 W	2700 K CRI 80	On/Off, 0-10V
LF8032.536-US-SLFB-700-830	[SLFB] Special linear, Forward throw - 106x28°	74058 lm	945 W	3000 K CRI 80	On/Off, 0-10V
LF8032.536-US-SLFB-700-840	[SLFB] Special linear, Forward throw - 106x28°	83090 lm	945 W	4000 K CRI 80	On/Off, 0-10V