

HANDRA Side - Ø2.4"


LH5007.595-US



22 mm
55/64"



40 mm
1 37/64"



[SLSH]

Special linear, Side
throw - 42x54°

Configurations

Light distribution	[SLSH] 42x54°
Delivered lumens flux	40 - 48 lm
Rated input power	1 W
Color temperature	2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 70, 4000 K CRI 80
Lifetime L90 (hour)	>102,000
Lifetime L80 (hour)	>102,000

Options

Product colors



Technical information

Housing	Corrosion resistant, die-cast, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Liquid gasket
Lens / Reflector	High reflectance aluminium coating
Glass / Diffusor	Custom Design PMMA Diffusor
Impact protection	IK10
Ingress protection	IP65
Input voltage	120-277V 50/60Hz
Insulation class	Class III
Weight	0.1 lbs
LED module	High power LEDs on metal-core PCB
Driver	External LED driver
Through wiring	Single power cord entry
Operating temperature	-25...50°C
Power cord	8" of flexible power cord
Packing box dimensions	2 3/4"*2 3/4"*2 3/4"

Accessories (To be ordered separately)

Mounting accessories



**0-10V Driver
within an IP67 box
for 1 to 6 HANDRA
modules**

007502066


Mounting accessories



**0-10V Driver
within an IP67 box
for 7 to 15
HANDRA modules**

007502067

Mounting accessories










**0-10V Driver
within an IP67 box
for 16 to 35
HANDRA modules**

007502068

Project name		Type		Quantity	
Date		Note			

LH5007.595-US-____-____-____-____-____

Light distribution	Rated input power	Color temperature	Control	Product colors
[SLSH] Special linear, Side throw - 42x54°	[350] 1 W	[827] 2700 K CRI 80 [830] 3000 K CRI 80 [740] 4000 K CRI 70 [840] 4000 K CRI 80		[HM1]  Black [HM2]  Dark gray [HM3]  Anthracite gray [HM4]  Light gray [HM5]  White [HM6]  Bronze [CC]  Custom color (Please specify RAL code)

Accessories (To be ordered separately)

Mounting accessories

[007502066]
 0-10V Driver within an IP67 box for 1 to 6 HANDRA modules

[007502067]
 0-10V Driver within an IP67 box for 7 to 15 HANDRA modules

[007502068]
 0-10V Driver within an IP67 box for 16 to 35 HANDRA modules

Configuration code	Light distribution	Delivered lumens flux	Rated input power	Color temperature	Control
LH5007.595-US-SLSH-350-740	[SLSH] Special linear, Side throw - 42x54°	48 lm	1 W	4000 K CRI 70	
LH5007.595-US-SLSH-350-827	[SLSH] Special linear, Side throw - 42x54°	40 lm	1 W	2700 K CRI 80	
LH5007.595-US-SLSH-350-830	[SLSH] Special linear, Side throw - 42x54°	40 lm	1 W	3000 K CRI 80	
LH5007.595-US-SLSH-350-840	[SLSH] Special linear, Side throw - 42x54°	40 lm	1 W	4000 K CRI 80	