L&C LUMINAIRE L 3 Module

LL2017.663-US

PHASED-OUT

[T2]
Type II - 130x85°

Configurations

Light distribution	[T2] 130x85°
Delivered lumens flux	8837 - 10691 lm
Rated input power	101 W
Color temperature	3000 K CRI 70, 3000 K CRI 80, 4000 K CRI 70
BUG rating	B2-U0-G1, B2-U0-G2
Lifetime L90 (hour)	>60, 000
Lifetime L80 (hour)	>60, 000

Options

Control	On/Off, 0-10V
Product colors	

Extras

External surge protection	10 kV
Connectivity	7 Pin NEMA socket
Luminaire body options	Double powder coating

Technical information

Mounting	Direct pole or side bracket mountable. Tenon: Ø2 1/4" x 4"
Housing	Corrosion resistant, die-cast, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	High reflectance aluminium coating, multifaceted micro reflector
Glass / Diffusor	Bio-based, enriched with bisphenol A diffusor
Impact protection	IK08
Ingress protection	IP66
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Wind catching area (EPA)	1.27 ft²
Weight	20 lbs
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	4/4 kV
Power factor	> 0.97
Through wiring	Single power cord entry
Operating temperature	-40...50°C
Power cord	20" of outdoor use rated flexible power cord

HEPER USA LLC
W227 N546 Westmound Drive Waukesha, 53186
Wisconsin, United States
+1 312 910 9740
infoUS@hepergroup.com

We reserve the right to change specifications without prior written notice. Edition: 28.12.2023. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

Project name		Type		Quantity	
Date		Note			

LL2017.663-US-___-___-___-___-___-___-___-___-___

Light distribution	Rated input power	Color temperature	Control	Product colors
[T2] Type II - 130x85°	**[700]** 101 W	**[730]** 3000 K CRI 70 **[830]** 3000 K CRI 80 **[740]** 4000 K CRI 70	**[ONOFF]** On/Off **[0-10V]** 0-10V	**[HM3]** Anthracite gray **[HM4]** Light gray **[CC]** Custom color (Please specify RAL code)

Extras
External surge protection
[SP10] 10 kV
Connectivity
[NM7] 7 Pin NEMA socket
Luminaire body options
[DPC] Double powder coating

HEPER USA LLC
W227 N546 Westmound Drive Waukesha, 53186
Wisconsin, United States
+1 312 910 9740
infoUS@hepergroup.com

We reserve the right to change specifications without prior written notice. Edition: 28.12.2023. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

Configuration code	Light distribution	Delivered lumens flux	Rated input power	Color temperature	Control
LL2017.663-US-T2-700-730	[T2] Type II - 130x85°	10691 lm	101 W	3000 K CRI 70	On/Off, 0-10V
LL2017.663-US-T2-700-740	[T2] Type II - 130x85°	10346 lm	101 W	4000 K CRI 70	On/Off, 0-10V
LL2017.663-US-T2-700-830	[T2] Type II - 130x85°	8837 lm	101 W	3000 K CRI 80	On/Off, 0-10V

HEPER USA LLC
W227 N546 Westmound Drive Waukesha, 53186
Wisconsin, United States
+1 312 910 9740
infoUS@hepergroup.com

We reserve the right to change specifications without prior written notice. Edition: 28.12.2023. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.