

URBAN UNITS V3 Top Module, 360°, 1 Module

LP4054.842-EN

CE UK
CA IK08 IP65



heper⁺



Variants

Options

Control

On/Off, DALI, AutoDIM

Product colours



Extras

Consult the factory

120-277V 50/60Hz

Technical information

Certificates

CE, UKCA

Housing

Corrosion resistant, marine grade aluminum housing

Finishing

Chromate conversion pretreatment followed by electrostatic powder coating

Fasteners

Stainless steel (AISI 304 / EN 1.4301 grade)

Gasket

Silicone

Glass / Diffusor

UV stable, bio-based polycarbonate diffusor

Impact protection

IK08

Ingress protection

IP65

Input voltage

220-240V 50/60Hz

Insulation class

Class I

Weight

14.7 kg

Driver

Integral LED driver

Driver surge protection

6/6 kV

Power factor

> 0.95

Through wiring

Single cable entry

Cable

0.2 m of flexible cable

HPR Pazarlama A.Ş.

Başkent OSB 22. Cd. No: 2, Malıköy, Temelli,
Sincan, 06909 Ankara, Turkey
+90 312 267 54 30
info@hepergroup.com

HEPER Europe GmbH

Ahornweg 5a, 58675
Hemer, Germany
+49 237 2901 2975
infoEU@hepergroup.com

We reserve the right to change specifications without prior written notice. Edition: 25.03.2024. For current version visit heperlighting.com. All flux ($\pm 7\%$ tolerance) and power values ($\pm 10\%$ tolerance) are derived following appropriate IES, CIE, and applicable standards.








Poles (Included)

Product specific poles with flange plate



Variant code	Height	Diameter / Dimensions	Spigot diameter
PAFC.C01.T001-H3	3m	Ø200mm	
PAFC.C01.T001-H4	4m	Ø200mm	
PAFC.C01.T001-H5	5m	Ø200mm	

Project name		Type		Quantity	
Date		Note			
LP4054.842-EN-__-__-__-__-EN-C1-__-__					

Light distribution	Rated input power	Colour temperature	Control	Product colours
			[ONOFF] On/Off [DALI] DALI [AUTO] AutoDIM	[HM1]  Black [HM2]  Dark grey [HM3]  Anthracite grey [HM4]  Light grey [HM5]  White [HM6]  Bronze [CC]  Custom colour (Please specify RAL code)
Extras				
Consult the factory				
[UNI] 120-277V 50/60Hz				