


# ZEROX S Dyno

LR9016.521-US



[WW]

Wall-wash - 46x25°

## Configurations

<b>Light distribution</b>	[WW] 46x25°
<b>Delivered lumens flux</b>	294 - 345 lm
<b>Rated input power</b>	4 W
<b>Color temperature</b>	2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 70, 4000 K CRI 80
<b>Lifetime L90 (hour)</b>	>42,000
<b>Lifetime L80 (hour)</b>	>42,000

## Options


<b>Control</b>	On/Off
<b>Product colors</b>	

## Technical information

<b>Mounting</b>	Ground recessed mountable
<b>Housing</b>	Corrosion resistant stainless steel housing (AISI 316L / EN 1.4571 grade)
<b>Fasteners</b>	Stainless steel (AISI 304 / EN 1.4301 grade)
<b>Gasket</b>	Silicone
<b>Lens / Reflector</b>	High reflectance aluminium coating, multifaceted micro reflector
<b>Glass / Diffuser</b>	Tempered safety glass
<b>Impact protection</b>	IK10
<b>Ingress protection</b>	IP67
<b>Input voltage</b>	120-277V 50/60Hz
<b>Insulation class</b>	Class I
<b>Weight</b>	6.1 lbs
<b>LED module</b>	High power LEDs on metal-core PCB
<b>Driver</b>	Internal LED driver
<b>Driver surge protection</b>	3/3 kV
<b>Power factor</b>	> 0.40
<b>Through wiring</b>	Single power cord entry
<b>Operating temperature</b>	-40...50°C
<b>Power cord</b>	12" of rubber-sheathed power cord

## Accessories (Included)

Mounting accessories



**Connector set - 5-pole**

141407400

## Accessories (To be ordered separately)


Mounting accessories



**Case removing vacuum**

160404012


Mounting accessories



**Plastic case for ZEROX S**

007502091

Project name		Type		Quantity	
Date		Note			
<b>LR9016.521-US-__-__-__-__-__</b>					

Light distribution	Rated input power	Color temperature	Control	Product colors
<b>[WW]</b> Wall-wash - 46x25°	<b>[350]</b> 4 W	<b>[827]</b> 2700 K CRI 80  <b>[830]</b> 3000 K CRI 80  <b>[740]</b> 4000 K CRI 70  <b>[840]</b> 4000 K CRI 80	<b>[ONOFF]</b> On/Off	<b>[SS]</b> Stainless steel 
<b>Accessories (Included)</b>	<b>Accessories (To be ordered separately)</b>			
<b>Mounting accessories</b>	<b>Mounting accessories</b>			
<b>[141407400]</b> Connector set - 5-pole	<b>[160404012]</b> Case removing vacuum  <b>[007502091]</b> Plastic case for ZEROX S			

<b>Configuration code</b>	<b>Light distribution</b>	<b>Delivered lumens flux</b>	<b>Rated input power</b>	<b>Color temperature</b>	<b>Control</b>
LR9016.521-US-WW-350-740	[WW] Wall-wash - 46x25°	345 lm	4 W	4000 K CRI 70	On/Off
LR9016.521-US-WW-350-827	[WW] Wall-wash - 46x25°	294 lm	4 W	2700 K CRI 80	On/Off
LR9016.521-US-WW-350-830	[WW] Wall-wash - 46x25°	303 lm	4 W	3000 K CRI 80	On/Off
LR9016.521-US-WW-350-840	[WW] Wall-wash - 46x25°	326 lm	4 W	4000 K CRI 80	On/Off