


GOLEDO-T 80 LED


LT2037.885-EN




IK08 IP66




[T-ASYM-A]
Tunnel, Asymmetric,
Type A -



[T-ASYM-B]
Tunnel, Asymmetric,
Type B -



[T-ASYM-C]
Tunnel, Asymmetric,
Type C -



[T-ASYM-D]
Tunnel, Asymmetric,
Type D -



[T-CB-A]
Tunnel, Counter
beam, Type A -



[T-CB-B]
Tunnel, Counter
beam, Type B -



[T-SYM-A]
Tunnel, Symmetric,
Type A -



[T-SYM-C]
Tunnel, Symmetric,
Type C -



[T-SYM-D]
Tunnel, Symmetric,
Type D -

Variants

Light distribution	[T-ASYM-A] , [T-ASYM-B] , [T-ASYM-C] , [T-ASYM-D] , [T-CB-A] , [T-CB-B] , [T-SYM-A] , [T-SYM-C] , [T-SYM-D]
Delivered lumens flux	11766 - 26600 lm
Rated input power	76 - 171 W
Colour temperature	3000 K CRI 70, 3000 K CRI 80, 4000 K CRI 70
Lifetime L90B50 (hour)	>102, 000
Lifetime L80B50 (hour)	>102, 000

Options

Control	On/Off, 0-10V, DALI, AutoDIM, StepDIM *
Product colours	

Extras

External surge protection	10 kV
Light output	Constant light output
Consult the factory	Class II, 120-277V 50/60Hz
Luminaire body options	Double powder coating

Technical information

Mounting	Standard strap connection. Sliding mounting bracket is optional through extra
Housing	Corrosion resistant, die-cast, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	PMMA lens with high optical efficiency
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP66
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	10.06 kg
LED module	High power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	10/6 kV
Power factor	> 0.95
Through wiring	Single cable entry
Operating temperature	-40...50°C
Cable	1 m of halogen-free cable
Notes	This product can be supplied with Insulation class (Class II) upon request. Please contact factory.

* Please check the specific variant for each control type.



HPR Pazarlama A.Ş.
Başkent OSB 22. Cd. No: 2, Malıköy, Temelli,
Sincan, 06909 Ankara, Turkey
+90 312 267 54 30
info@hepergroup.com

HEPER Europe GmbH
Ahornweg 5a, 58675
Hemer, Germany
+49 237 2901 2975
infoEU@hepergroup.com

We reserve the right to change specifications without prior written notice. Edition: 04.04.2024.
For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

Project name		Type		Quantity	
Date		Note			

LT2037.885-EN-____-____-____-____-____**-EN-C1-**____-____-____-____-____

Light distribution	Rated input power	Colour temperature	Control	Product colours
[T-ASYM-A] Tunnel, Asymmetric, Type A	[350] 76 W	[730] 3000 K CRI 70	[ONOFF] On/Off	[CC]  Custom colour (Please specify RAL code)
[T-ASYM-B] Tunnel, Asymmetric, Type B	[350] 77 W	[830] 3000 K CRI 80	[0-10V] 0-10V	[7035]  Light grey (RAL 7035)
[T-ASYM-C] Tunnel, Asymmetric, Type C	[350] 78 W	[740] 4000 K CRI 70	[DALI] DALI	
[T-ASYM-D] Tunnel, Asymmetric, Type D	[350] 79 W		[AUTO] AutoDIM	
[T-CB-A] Tunnel, Counter beam, Type A	[500] 112 W		[STEP] StepDIM	
[T-CB-B] Tunnel, Counter beam, Type B	[500] 113 W			
[T-SYM-A] Tunnel, Symmetric, Type A	[500] 114 W			
[T-SYM-C] Tunnel, Symmetric, Type C	[500] 115 W			
[T-SYM-D] Tunnel, Symmetric, Type D	[500] 116 W			
	[700] 171 W			

Extras

External surge protection
[SP10] 10 kV
Light output
[CLO] Constant light output
Consult the factory
[C2] Class II
[UNI] 120-277V 50/60Hz
Luminaire body options
[DPC] Double powder coating

Variant code	Light distribution	Delivered lumens flux	Rated input power	Colour temperature	Control
LT2037.885-EN-T-ASYM-A-350-730	[T-ASYM-A] Tunnel, Asymmetric, Type A	12307 lm	77 W	3000 K CRI 70	
LT2037.885-EN-T-ASYM-A-350-740	[T-ASYM-A] Tunnel, Asymmetric, Type A	13809 lm	78 W	4000 K CRI 70	
LT2037.885-EN-T-ASYM-A-350-830	[T-SYM-A] Tunnel, Symmetric, Type A			3000 K CRI 80	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-ASYM-A-500-730	[T-ASYM-A] Tunnel, Asymmetric, Type A	17065 lm	114 W	3000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-ASYM-A-500-740	[T-ASYM-A] Tunnel, Asymmetric, Type A	19075 lm	115 W	4000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-ASYM-A-700-730	[T-ASYM-A] Tunnel, Asymmetric, Type A	23705 lm	171 W	3000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-ASYM-A-700-740	[T-ASYM-A] Tunnel, Asymmetric, Type A	26280 lm	171 W	4000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-ASYM-A-700-830	[T-ASYM-A] Tunnel, Asymmetric, Type A	12305 lm	77 W	3000 K CRI 80	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-ASYM-B-350-730	[T-ASYM-B] Tunnel, Asymmetric, Type B	12056 lm	76 W	3000 K CRI 70	
LT2037.885-EN-T-ASYM-B-350-740	[T-ASYM-B] Tunnel, Asymmetric, Type B	13529 lm	77 W	4000 K CRI 70	
LT2037.885-EN-T-ASYM-B-500-730	[T-ASYM-B] Tunnel, Asymmetric, Type B	16715 lm	112 W	3000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-ASYM-B-500-740	[T-ASYM-B] Tunnel, Asymmetric, Type B	18685 lm	113 W	4000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-ASYM-B-700-730	[T-ASYM-B] Tunnel, Asymmetric, Type B	23705 lm	171 W	3000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-ASYM-B-700-740	[T-ASYM-B] Tunnel, Asymmetric, Type B	26210 lm	171 W	4000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-ASYM-C-350-730	[T-ASYM-C] Tunnel, Asymmetric, Type C	12360 lm	77 W	3000 K CRI 70	
LT2037.885-EN-T-ASYM-C-350-740	[T-ASYM-C] Tunnel, Asymmetric, Type C	13872 lm	78 W	4000 K CRI 70	
LT2037.885-EN-T-ASYM-C-500-730	[T-ASYM-C] Tunnel, Asymmetric, Type C	17135 lm	114 W	3000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-ASYM-C-500-740	[T-ASYM-C] Tunnel, Asymmetric, Type C	19160 lm	114 W	4000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-ASYM-C-700-730	[T-ASYM-C] Tunnel, Asymmetric, Type C	23810 lm	171 W	3000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM

HPR Pazarlama A.Ş.

Başkent OSB 22. Cd. No: 2, Malıköy, Temelli,
Sincan, 06909 Ankara, Turkey
+90 312 267 54 30
info@hepergroup.com

HEPER Europe GmbH

Ahornweg 5a, 58675
Hemer, Germany
+49 237 2901 2975
infoEU@hepergroup.com

We reserve the right to change specifications without prior written notice. Edition: 04.04.2024.
For current version visit heperlighting.com. All flux ($\pm 7\%$ tolerance) and power values ($\pm 10\%$ tolerance) are derived following appropriate IES, CIE, and applicable standards.

LT2037.885-EN-T-ASYM-C-700-740	[T-ASYM-C] Tunnel, Asymmetric, Type C	26600 lm	171 W	4000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-ASYM-D-350-730	[T-ASYM-D] Tunnel, Asymmetric, Type D	12360 lm	77 W	3000 K CRI 70	
LT2037.885-EN-T-ASYM-D-350-740	[T-ASYM-D] Tunnel, Asymmetric, Type D	13301 lm	77 W	4000 K CRI 70	
LT2037.885-EN-T-ASYM-D-500-730	[T-ASYM-D] Tunnel, Asymmetric, Type D	17135 lm	114 W	3000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-ASYM-D-500-740	[T-ASYM-D] Tunnel, Asymmetric, Type D	18375 lm	114 W	4000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-ASYM-D-700-730	[T-ASYM-D] Tunnel, Asymmetric, Type D	23810 lm	171 W	3000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-ASYM-D-700-740	[T-ASYM-D] Tunnel, Asymmetric, Type D	25545 lm	171 W	4000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-CB-A-350-730	[T-CB-A] Tunnel, Counter beam, Type A	12283 lm	77 W	3000 K CRI 70	
LT2037.885-EN-T-CB-A-350-740	[T-CB-A] Tunnel, Counter beam, Type A	13780 lm	78 W	4000 K CRI 70	
LT2037.885-EN-T-CB-A-350-830	[T-CB-A] Tunnel, Counter beam, Type A			3000 K CRI 80	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-CB-A-500-730	[T-CB-A] Tunnel, Counter beam, Type A	17030 lm	114 W	3000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-CB-A-500-740	[T-CB-A] Tunnel, Counter beam, Type A	19035 lm	115 W	4000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-CB-A-700-730	[T-CB-A] Tunnel, Counter beam, Type A	23655 lm	171 W	3000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-CB-A-700-740	[T-CB-A] Tunnel, Counter beam, Type A	26125 lm	171 W	4000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-CB-B-350-730	[T-CB-B] Tunnel, Counter beam, Type B	11896 lm	77 W	3000 K CRI 70	
LT2037.885-EN-T-CB-B-350-740	[T-CB-B] Tunnel, Counter beam, Type B	13350 lm	78 W	4000 K CRI 70	
LT2037.885-EN-T-CB-B-500-730	[T-CB-B] Tunnel, Counter beam, Type B	16495 lm	114 W	3000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-CB-B-500-740	[T-CB-B] Tunnel, Counter beam, Type B	18435 lm	114 W	4000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-CB-B-700-730	[T-CB-B] Tunnel, Counter beam, Type B	22910 lm	171 W	3000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-CB-B-700-740	[T-CB-B] Tunnel, Counter beam, Type B	25590 lm	171 W	4000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-SYM-A-350-730	[T-SYM-A] Tunnel, Symmetric, Type A	12123 lm	77 W	3000 K CRI 70	
LT2037.885-EN-T-SYM-A-350-740	[T-SYM-A] Tunnel, Symmetric, Type A	13602 lm	78 W	4000 K CRI 70	

HPR Pazarlama A.Ş.

Başkent OSB 22. Cd. No: 2, Malıköy, Temelli,
Sincan, 06909 Ankara, Turkey
+90 312 267 54 30
info@hepergroup.com

HEPER Europe GmbH

Ahornweg 5a, 58675
Hemer, Germany
+49 237 2901 2975
infoEU@hepergroup.com

We reserve the right to change specifications without prior written notice. Edition: 04.04.2024.
For current version visit heperlighting.com. All flux ($\pm 7\%$ tolerance) and power values ($\pm 10\%$ tolerance) are derived following appropriate IES, CIE, and applicable standards.

LT2037.885-EN-T-SYM-A-350-830	[T-SYM-A] Tunnel, Symmetric, Type A			3000 K CRI 80	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-SYM-A-500-730	[T-SYM-A] Tunnel, Symmetric, Type A	16810 lm	114 W	3000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-SYM-A-500-740	[T-SYM-A] Tunnel, Symmetric, Type A	18790 lm	115 W	4000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-SYM-A-700-730	[T-SYM-A] Tunnel, Symmetric, Type A	23345 lm	171 W	3000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-SYM-A-700-740	[T-SYM-A] Tunnel, Symmetric, Type A	25775 lm	171 W	4000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-SYM-C-350-730	[T-SYM-C] Tunnel, Symmetric, Type C	11988 lm	77 W	3000 K CRI 70	
LT2037.885-EN-T-SYM-C-350-740	[T-SYM-C] Tunnel, Symmetric, Type C	13678 lm	78 W	4000 K CRI 70	
LT2037.885-EN-T-SYM-C-500-730	[T-SYM-C] Tunnel, Symmetric, Type C	16620 lm	114 W	3000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-SYM-C-500-740	[T-SYM-C] Tunnel, Symmetric, Type C	18890 lm	114 W	4000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-SYM-C-700-730	[T-SYM-C] Tunnel, Symmetric, Type C	23090 lm	171 W	3000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-SYM-C-700-740	[T-SYM-C] Tunnel, Symmetric, Type C	26195 lm	171 W	4000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-SYM-D-350-730	[T-SYM-D] Tunnel, Symmetric, Type D	11766 lm	77 W	3000 K CRI 70	
LT2037.885-EN-T-SYM-D-350-740	[T-SYM-D] Tunnel, Symmetric, Type D	13201 lm	79 W	4000 K CRI 70	
LT2037.885-EN-T-SYM-D-500-730	[T-SYM-D] Tunnel, Symmetric, Type D	16305 lm	114 W	3000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-SYM-D-500-740	[T-SYM-D] Tunnel, Symmetric, Type D	18230 lm	116 W	4000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-SYM-D-700-730	[T-SYM-D] Tunnel, Symmetric, Type D	22655 lm	171 W	3000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM
LT2037.885-EN-T-SYM-D-700-740	[T-SYM-D] Tunnel, Symmetric, Type D	24930 lm	171 W	4000 K CRI 70	On/Off, 0-10V, DALI, AutoDIM, StepDIM

HPR Pazarlama A.Ş.

Başkent OSB 22. Cd. No: 2, Malıköy, Temelli,
Sincan, 06909 Ankara, Turkey
+90 312 267 54 30
info@hepergroup.com

HEPER Europe GmbH

Ahornweg 5a, 58675
Hemer, Germany
+49 237 2901 2975
infoEU@hepergroup.com

We reserve the right to change specifications without prior written notice. Edition: 04.04.2024.
For current version visit heperlighting.com. All flux ($\pm 7\%$ tolerance) and power values ($\pm 10\%$ tolerance) are derived following appropriate IES, CIE, and applicable standards.