


IN-LIGHT ML 2 Module

LW2029.672-US



PHASED-OUT



[EL]

Elliptical - 130x85°

Configurations

Light distribution	[EL] 130x85°
Delivered lumens flux	5280 - 7950 lm
Rated input power	68 W
Color temperature	3000 K CRI 80, 4000 K CRI 70
BUG rating	B2-U0-G1
Lifetime L90 (hour)	>60,000
Lifetime L80 (hour)	>60,000

Options

Control	On/Off, 0-10V
Product colors	

Extras








Luminaire body options	Double powder coating
-------------------------------	-----------------------

Technical information

Mounting	Direct tray mountable
Housing	Corrosion resistant, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	High reflectance aluminium coating, multifaceted micro reflector
Glass / Diffusor	Bio-based, enriched with bisphenol A diffusor
Impact protection	IK08
Ingress protection	IP66
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Weight	8.7 lbs
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	6/4 kV
Power factor	> 0.98
Through wiring	Single power cord entry
Operating temperature	-40...50°C
Power cord	40" of halogen-free power cord

Project name		Type		Quantity	
Date		Note			

LW2029.672-US- _ _ _ _ _

Light distribution	Rated input power	Color temperature	Control	Product colors
[EL] Elliptical - 130x85°	[500] 68 W	[830] 3000 K CRI 80 [740] 4000 K CRI 70	[ONOFF] On/Off [0-10V] 0-10V	[HM1]  Black [HM2]  Dark gray [HM3]  Anthracite gray [HM4]  Light gray [HM5]  White [HM6]  Bronze [CC]  Custom color (Please specify RAL code)
Extras				
Luminaire body options				
[DPC] Double powder coating				

Configuration code	Light distribution	Delivered lumens flux	Rated input power	Color temperature	Control
LW2029.672-US-EL-500-740	[EL] Elliptical - 130x85°	5677 lm	68 W	4000 K CRI 70	On/Off, 0-10V
LW2029.672-US-EL-500-830	[EL] Elliptical - 130x85°	5280 lm	68 W	3000 K CRI 80	On/Off, 0-10V
LW2029.672-US-EL-700-740	[EL] Elliptical - 130x85°	7950 lm	68 W	4000 K CRI 70	On/Off, 0-10V
LW2029.672-US-EL-700-830	[EL] Elliptical - 130x85°	7394 lm	68 W	3000 K CRI 80	On/Off, 0-10V