

## **VEGAS**

# heper "

#### LF8020.693-EN-S-700-740









**[S]** Spot - NEMA Type 0

## Configuration

**Light distribution** [S] 7° **Delivered lumens flux** 1019 lm Rated input power 10 W **Color temperature** 4000 K CRI 70 **Luminaire efficacy** 101 lm/W Lamp 1 LED **Color Deviation** 5 SDCM Lifetime L90 (hour) >72,600 >72,600 Lifetime L80 (hour)

#### Options

#### Technical information

Mounting	Yoke mount (standard), stake mount (optional)
Tilt angle	+60°/-30°
Housing	Corrosion resistant, die-cast, marine grade
	aluminum housing
Finishing	Chromate conversion pretreatment followed by
	electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Liquid silicone
Lens / Reflector	High reflectance aluminium coating [S] [N],
	PMMA lens with high optical efficiency [MN] [M]
Glass / Diffusor	Tempered safety glass
Impact protection	IK07
Ingress protection	IP65
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	2.07 kg
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	1/1 kV
protection	
Power factor	> 0.91

Through wiring
Single power cord entry
Operating
-25...50°C

temperature

**Power cord** 20" of outdoor use rated flexible power cord

# Accessories (To be ordered separately)

Optical accessories

Mounting accessories





Visor for VEGA S

100708016

**Spike** 160405040

Project na	me		Туре	Quantity	
Date		Note			

# LF8020.693-EN-S-700-740-\_\_--\_\_-

Light distribution	Rated input power	Color temperature	Control	Product colors
[S] Spot - NEMA Type 0 -	[ <b>700]</b> 10 W	[ <b>740]</b> 4000 K CRI 70	[ONOFF] On/Off	[HM1] Black
7°  [N] Narrow - NEMA Type 2 - 26°  [MN] Medium narrow - NEMA Type 3 - 42°  [M] Medium - NEMA Type 4 - 60°		[827] 2700 K CRI 80 [830] 3000 K CRI 80 [840] 4000 K CRI 80	[DALI] DALI	[HM2] Dark gray  [HM3] Anthracite gray  [HM4] Light gray  [HM5] White  [HM6] Bronze  [CC] Custom color (Please specify RAL code)
Extras	Accessories (To be ordered separately)			I
Consult the factory	Optical accessories			
<b>[UNI]</b> 120-277V 50/60Hz	[100708016] Visor for VEGA S			
Luminaire body options	Mounting accessories			
[DPC] Double powder coating	[ <b>160405040</b> ] Spike			