
C-LIGHT AFX 4 Module



LC2029.864-EN-T5-350-827









Type V

Configuration

| Light distribution | [T5] 117° |
|-----------------------|---------------|
| Delivered lumens flux | 8230 lm |
| Rated input power | 68 W |
| Color temperature | 2700 K CRI 80 |
| Luminaire efficacy | 121 lm/W |
| Lamp | 64 LED |
| Color Deviation | 3 SDCM |
| BUG rating | B3-U0-G0 |
| Lifetime L90 (hour) | >102,000 |
| Lifetime L80 (hour) | >102,000 |

Options

Notes

Technical information

| Mounting | Catenary wire mounting |
|--------------------|--|
| Housing | Corrosion resistant, die-cast, marine grade |
| - | aluminum housing |
| Finishing | Chromate conversion pretreatment followed by |
| - | electrostatic powder coating |
| Fasteners | Stainless steel (AISI 304 / EN 1.4301 grade) |
| Gasket | Liquid silicone |
| Lens / Reflector | PMMA lens with high optical efficiency |
| Glass / Diffusor | Tempered safety glass |
| Impact protection | IK08 |
| Ingress protection | IP66 |
| Input voltage | 220-240V 50/60Hz |
| Insulation class | Class I |
| Weight | 8.8 kg |
| LED module | High power LEDs on metal-core PCB |
| Driver | Internal LED driver |
| Driver surge | 10/6 kV |
| protection | |
| Power factor | > 0.95 |
| Through wiring | Single power cord entry |
| Operating | -4050°C |
| temperature | |
| Power cord | 20" of outdoor use rated flexible power cord |
| Packing box | 80*20*25 cm |
| dimensions | |
| unicisions | |

This product can be supplied with Insulation class (Class II) upon request. Please contact factory.

HEPER USA LLC W227 N546 Westmound Drive Waukesha, 53186 Wisconsin, United States +1 312 910 9740 infoUS@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 18.05.2024. For current version visit heperlighting.com. All flux (\pm %7 tolerance) and power values (\pm %10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

| Project name | | | Туре | Quantity | | | |
|--------------------------|--|------|------|----------|--|--|--|
| Date | | Note | | | | | |
| LC2029.864-EN-T5-350-827 | | | | | | | |

| Light distribution | Rated input power | Color temperature | Control | Product colors |
|------------------------------|-----------------------|--|--------------------------|--------------------------------|
| [T5] Type V - 117° | [350] 68 W | [827] 2700 K CRI 80 | [ONOFF] On/Off | [HM3] Anthracite gray |
| | [500] 97 W | [830] 3000 K CRI 80 | [DALI] DALI | [HM4] Light gray |
| | [700] 135 W | [740] 4000 K CRI 70 [840] 4000 K CRI 80 | | [CC] (Please specify RAL code) |
| Extras | | | - | · |
| Consult the factory | | | | |
| [C2] Class II | | | | |
| TUNIT | | | | |

[UNI] 120-277V 50/60Hz

Luminaire body options

[DPC]

Double powder coating