

C-LIGHT AFX 4 Module

LC2029.864-US-T5-350-840











[T5] Type V

Configuration

Light distribution [T5] 117° Delivered lumens flux 8230 lm Rated input power 68 W **Color temperature** 4000 K CRI 80 **Luminaire efficacy** 121 lm/W Lamp 64 LED **Color Deviation** 4 SDCM B3-U0-G0 **BUG** rating Lifetime L90 (hour) >102,000 Lifetime L80 (hour) >102,000

Options

Technical information

MountingCatenary wire mountingHousingCorrosion resistant, die-cast, marine grade

aluminum housing

Finishing Chromate conversion pretreatment followed by

electrostatic powder coating

Fasteners Stainless steel (AISI 304 / EN 1.4301 grade) **Gasket** Liquid silicone

Lens / Reflector PMMA lens with high optical efficiency
Glass / Diffusor Tempered safety glass

Glass / DiffusorTempered safety glassImpact protectionIK08Ingress protectionIP66Input voltage120-277V 50/60Hz

Insulation class Class I

Weight 19.36 lbs

LED module High power LEDs on metal-core PCB

Driver Internal LED driver

Driver surge 10/6 kV

Driver surge protection

Power factor > 0.95
Through wiring Single power cord entry
Operating -40...50°C

temperature

Power cord 20" of outdoor use rated flexible power cord

Packing box 31 1/2"*7 7/8"*9 27/32"

dimensions

and applicable standards.

Project name					Туре	Quantity	
Date			Note				

LC2029.864-US-T5-350-840-__--_

Light distribution	Rated input power	Color temperature	Control	Product colors
[T5] Type V - 117°	[350] 68 W	[840] 4000 K CRI 80	[ONOFF] On/Off	[HM3] Anthracite gray
	[500] 97 W	[827] 2700 K CRI 80	[0-10V] 0-10V	[HM4] Light gray
	[700] 135 W	[830] 3000 K CRI 80		[CC] &
		[740] 4000 K CRI 70		specify RAL code)

Extras

Luminaire body options

[DPC]

Double powder coating