
DOMINO W AFX 1 Module




LW7031.861-EN-P4-700-740





4 23/32"





[P4] Pedestrian crosswalk distribution

Configuration

Light distribution	[P4] 20x78°
Delivered lumens flux	4480 lm
Rated input power	35 W
Color temperature	4000 K CRI 70
Luminaire efficacy	128 lm/W
Lamp	16 LED
Color Deviation	4 SDCM
BUG rating	B1-U0-G1
Lifetime L90 (hour)	>102,000
Lifetime L80 (hour)	>102,000

Options

dimensions

Technical information

Mounting	Surface or wall mountable
Housing	Corrosion resistant, marine grade aluminum
	housing
Finishing	Chromate conversion pretreatment followed by
	electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Liquid silicone
Lens / Reflector	PMMA lens with high optical efficiency
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP66
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	5.0 kg
LED module	High power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	10/6 kV
protection	
Power factor	> 0.95
Through wiring	Single power cord entry
Operating	-4050°C
temperature	
Power cord	8" of flexible power cord
Packing box	20*16*77 cm

HEPER USA LLC W227 N546 Westmound Drive Waukesha, 53186 Wisconsin, United States +1 312 910 9740 infoUS@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 19.05.2024. For current version visit heperlighting.com. All flux (\pm %7 tolerance) and power values (\pm %10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

Project na	me			Туре	Quantity
Date			Note		
LW7031	.861-EN-F	P4-700-74	0		

Light distribution	Rated input power	Color temperature	Control	Product colors
[P4] Pedestrian crosswalk	[700] 35 W	[740] 4000 K CRI 70	[ONOFF] On/Off	[HM1] Black
distribution - 20x78° [T1] Type I - 111x48°	[350] 18 W	[827] 2700 K CRI 80	[DALI] DALI	[HM2] Dark gray
[T2] Type II - 133x48°	[500] 25 W	[830] 3000 K CRI 80	[AUTO] AutoDIM	[HM3] Anthracite gray
[T2] Type II - 149x54°		[840] 4000 K CRI 80	[STEP] StepDIM	[HM4] Light gray
[T3] Type III - 143x63°				[HM5] White
[T4] Type IV - 117x64°				[HM6] Bronze
[T5] Type V - 117°				[CC] Custom color (Plea specify RAL code)
Extras				
Light output				
[BS] Backlight Shield				
Consult the factory				
IUNII				

[UNI] 120-277V 50/60Hz

Luminaire body options

[DPC]

Double powder coating