

DOMINO W AFX 1 Module

LW7031.861-EN-T1-700-827









[T1] Type I

Configuration

Light distribution	[T1] 111x48°
Delivered lumens flux	3750 lm
Rated input power	35 W
Color temperature	2700 K CRI 80
Luminaire efficacy	107 lm/W
Lamp	16 LED
Color Deviation	3 SDCM
BUG rating	B2-U0-G1
Lifetime L90 (hour)	>102,000
Lifetime L80 (hour)	>102,000

Options

Technical information

Mounting	Surface or wall mountable
Housing	Corrosion resistant, marine grade aluminum
	housing
Finishing	Chromate conversion pretreatment followed by
	electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)

Liquid silicone Gasket PMMA lens with high optical efficiency Lens / Reflector Glass / Diffusor Tempered safety glass Impact protection Ingress protection IP66 Input voltage 220-240V 50/60Hz

Insulation class Class I 5.0 kg Weight **LED** module High power LEDs on metal-core PCB

Driver Internal LED driver **Driver surge**

10/6 kV

protection **Power factor** > 0.95 Through wiring Single power cord entry Operating -40...50°C

8" of flexible power cord Power cord **Packing box** 20*16*77 cm

dimensions

temperature

Project name			Туре	Quantity	
Date	N	lote			

LW7031.861-EN-T1-700-827-__--_--

Light distribution	Rated input power	Color temperature	Control	Product colors
[T1] Type I - 111x48°	[700] 35 W	[827] 2700 K CRI 80	[ONOFF] On/Off	[HM1] Black
[P4] Pedestrian crosswalk	[350] 18 W	[830] 3000 K CRI 80	[DALI] DALI	[HM2] Dark gray
distribution - 20x78° [T2]	[500] 25 W	[740] 4000 K CRI 70	[AUTO] AutoDIM	[HM3] Anthracite gray
Type II - 133x48° [T2] Type II - 149x54°		[840] 4000 K CRI 80	[STEP] StepDIM	[HM4] Light gray
[T3] Type III - 143x63°				[HM5] White
[T4] Type IV - 117x64°				[HM6] Bronze
[T5] Type V - 117°				[CC] Custom color (Please specify RAL code)

ras

Light output

[BS]

Backlight Shield

Consult the factory

[UNI]

120-277V 50/60Hz

Luminaire body options

[DPC]

Double powder coating