

DOMINO W AFX 1 Module

heper t

LW7031.861-US-T5-350-830









[T5] Type V

Configuration

Light distribution [T5] 117° Delivered lumens flux 2055 lm Rated input power 18 W **Color temperature** 3000 K CRI 80 **Luminaire efficacy** 114 lm/W Lamp 16 LED **Color Deviation** 3 SDCM B1-U0-G0 **BUG** rating Lifetime L90 (hour) >102,000 Lifetime L80 (hour) >102,000

Options

temperature

Technical information

MountingSurface or wall mountableHousingCorrosion resistant, marine grade aluminum
housingFinishingChromate conversion pretreatment followed by
electrostatic powder coatingFastenersStainless steel (AISI 304 / EN 1.4301 grade)

Gasket Liquid silicone
Lens / Reflector PMMA lens with high optical efficiency
Glass / Diffusor Tempered safety glass
Impact protection IK08
Ingress protection IP66

Input voltage120-277V 50/60HzInsulation classClass IWeight11 lbs

LED module

Driver

Driver

Driver

Driver

Driver

LEDs on metal-core PCB

Internal LED driver

10/6 kV

protection

Power factor > 0.95
Through wiring Single power cord entry
Operating -40...50°C

Power cord8" of flexible power cordNotes3000K CCT or warmer must be selected to beDarkSky International certified.

and applicable standards.

Project name				Туре	Quantity	
Date		Note				

LW7031.861-US-T5-350-830-__--__-

Light distribution	Rated input power	Color temperature	Control	Product colors
[T5] Type V - 117°	[350] 18 W	[830] 3000 K CRI 80	[ONOFF] On/Off	[HM1] Black
[P4] Pedestrian crosswalk distribution - 20x78°	[500] 25 W	[827] 2700 K CRI 80	[0-10V] 0-10V	[HM2] Dark gray
[T1] Type I - 111x48°	[700] 35 W	[740] 4000 K CRI 70 [840] 4000 K CRI 80		[HM3] Anthracite gray
[T2] Type II - 133x48°				[HM4] Light gray
[T2] Type II - 149x54°				[HM5] White
[T3] Type III - 143x63°				[HM6] Bronze
[T4] Type IV - 117x64°				[CC] Custom color (Please specify RAL code)

Extr	as
------	----

Connectivity

[NM7]

7 Pin NEMA socket

Consult the factory

[MS]

Motion sensor

Luminaire body options

[DPC]

Double powder coating