

OLIVA ML EVO 2 Module

CE UK CA IK08 IP66



LL2002.682-EN-T2-700-740-ONOFF-EN-C1



PHASED-
OUT



[T2]

Type II, Asymmetric,
Side throw

Variant

Light distribution	[T2] 130x85°
Delivered lumens flux	7950 lm
Rated input power	68 W
Colour temperature	4000 K CRI 70
Luminaire efficacy	114 lm/W
Lamp	8 LED
MacAdam Ellipse	3 SDCM
BUG rating	B2-U0-G1
Photobiological safety	Risk group 0
Lifetime L90B50 (hour)	>60,000
Lifetime L80B50 (hour)	>60,000

Options

Technical information

Mounting	Direct pole or side bracket mountable. Spigot: Ø60 mm x 100 mm
Tilt angle	+15°/-15°
Housing	Corrosion resistant, die-cast, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Liquid silicone
Lens / Reflector	High reflectance aluminium coating, multifaceted micro reflector
Glass / Diffusor	Bio-based, enriched with bisphenol A diffusor
Impact protection	IK08
Ingress protection	IP66
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Wind catching area (EPA)	0.42 m ²
Weight	15 kg
LED module	Multi-chip high power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	6/6 kV
Power factor	> 0.95
Through wiring	Single cable entry
Operating temperature	-40...50°C
Cable	0.5 m of flexible cable
Notes	LED ring will be delivered with Red light colour (R1) as standard. Please check Extras for Green (G1) and Blue (B1).

Project name		Type		Quantity	
Date		Note			
LL2002.682-EN-T2-700-740-ONOFF-EN-C1-__-__-__-__-__					

Light distribution	Rated input power	Colour temperature	Control	Product colours
[T2] Type II, Asymmetric, Side throw - 130x85°	[700] 68 W	[740] 4000 K CRI 70	[ONOFF] On/Off	[HM1] Black
		[830] 3000 K CRI 80		[HM2] Dark grey
				[HM3] Anthracite grey
				[HM4] Light grey
				[HM5] White
				[HM6] Bronze
				[CC] Custom colour (Please specify RAL code)

Extras
External surge protection
[SP10] 10 kV
Light output
[B1] LED ring with Blue light colour
[G1] LED ring with Green light colour
Consult the factory
[UNI] 120-277V 50/60Hz
Luminaire body options
[DPC] Double powder coating