


TILA S AFX 1 Module

CE UK CA IK08 IP66



LL2030.861-EN-T2-2-700-840-ONOFF-EN-C1



[T2]

Type II, Asymmetric,
Side throw

Variant

Light distribution	[T2] 149x54°
Delivered lumens flux	3665 lm
Rated input power	35 W
Colour temperature	4000 K CRI 80
Luminaire efficacy	104 lm/W
Lamp	16 LED
MacAdam Ellipse	4 SDCM
BUG rating	B1-U0-G1
Lifetime L90B50 (hour)	>102,000
Lifetime L80B50 (hour)	>102,000

Options

Technical information

Mounting	Direct pole or side bracket mountable. Spigot: Ø60 mm x 100 mm
Housing	Corrosion resistant, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Liquid silicone
Lens / Reflector	PMMA lens with high optical efficiency
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP66
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	19.42 kg (3 m), 22.66 kg (4 m)
LED module	High power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	10/6 kV
Power factor	> 0.95
Through wiring	Single cable entry
Operating temperature	-40...50°C
Cable	0.5 m of flexible cable
Packing box dimensions	40*35*7 cm
Pole detail	Poles are supplied with flange plate. Flange cover and anchorage can be ordered separately. Embedded base is optional
Notes	QUICK SHIP: Some variants will be delivered faster. Please consult the factory.

Poles (Included)

Product specific poles with flange plate



Variant code	Height	Diameter / Dimensions	Spigot diameter
PAFD.R02.T001.T00 2-H3	3m	120*80mm	
PAFD.R02.T001.T00 2-H4	4m	120*80mm	

Project name		Type		Quantity	
Date		Note			
LL2030.861-EN-T2-2-700-840-ONOFF-EN-C1-__-__-__-__					

Light distribution	Rated input power	Colour temperature	Control	Product colours
[T2] Type II, Asymmetric, Side throw - 149x54°	[700] 35 W	[840] 4000 K CRI 80	[ONOFF] On/Off	[HM1]  Black
[P4] Special pedestrian road distribution-right side traffic - 20x78°	[350] 18 W	[827] 2700 K CRI 80		[HM2]  Dark grey
[T1] Type I, Asymmetric, Side throw - 111x48°	[500] 25 W	[830] 3000 K CRI 80		[HM3]  Anthracite grey
[T2] Type II, Asymmetric, Side throw - 133x48°		[740] 4000 K CRI 70		[HM4]  Light grey
[T3] Type III, Asymmetric, Side throw - 143x63°				[HM5]  White
[T4] Type IV, Asymmetric, Forward throw - 117x64°				[HM6]  Bronze
[T5] Type V, Symmetric - 117°				[CC]  Custom colour (Please specify RAL code)
Height	Extras			
[H3] 3m	Consult the factory			
[H4] 4m	[UNI] 120-277V 50/60Hz			
[HC]	Luminaire body options			
	[DPC] Double powder coating			