

# RHINO AFX 1 Module



IK08 IP66



LL2028.861-EN-T4-500-827-EN-C1



[T4]

Type IV, Asymmetric,  
Forward throw

## Variant

|                        |               |
|------------------------|---------------|
| Light distribution     | [T4] 117x64°  |
| Delivered lumens flux  | 2805 lm       |
| Rated input power      | 25 W          |
| Colour temperature     | 2700 K CRI 80 |
| Luminaire efficacy     | 112 lm/W      |
| Lamp                   | 16 LED        |
| MacAdam Ellipse        | 3 SDCM        |
| BUG rating             | B1-U0-G1      |
| Lifetime L90B50 (hour) | >102,000      |
| Lifetime L80B50 (hour) | >102,000      |

## Options

## Technical information

|                             |                                                                              |
|-----------------------------|------------------------------------------------------------------------------|
| Mounting                    | Direct pole or side bracket mountable. Spigot:<br>Ø60 mm x 100 mm            |
| Tilt angle                  | +70°/-30°                                                                    |
| Housing                     | Corrosion resistant, die-cast, marine grade<br>aluminum housing              |
| Finishing                   | Chromate conversion pretreatment followed by<br>electrostatic powder coating |
| Fasteners                   | Stainless steel (AISI 304 / EN 1.4301 grade)                                 |
| Gasket                      | Liquid silicone                                                              |
| Lens / Reflector            | PMMA lens with high optical efficiency                                       |
| Glass / Diffuser            | Tempered safety glass                                                        |
| Impact protection           | IK08                                                                         |
| Ingress protection          | IP66                                                                         |
| Input voltage               | 220-240V 50/60Hz                                                             |
| Insulation class            | Class I                                                                      |
| Wind catching area<br>(EPA) | 0,08 m <sup>2</sup>                                                          |
| Weight                      | 6.73 kg                                                                      |
| LED module                  | High power LEDs on metal-core PCB                                            |
| Driver                      | Internal LED driver                                                          |
| Driver surge<br>protection  | 6/6 kV                                                                       |
| Power factor                | > 0.95                                                                       |
| Through wiring              | Single cable entry                                                           |
| Operating<br>temperature    | -40...50°C                                                                   |
| Cable                       | 0.5 m of flexible cable                                                      |
| Packing box<br>dimensions   | 32*32*32 cm                                                                  |

HPR Pazarlama A.Ş.  
Başkent OSB 22. Cd. No: 2, Malıköy, Temelli,  
Sincan, 06909 Ankara, Turkey  
+90 312 267 54 30  
info@hepergroup.com

HEPER Europe GmbH  
Ahornweg 5a, 58675  
Hemer, Germany  
+49 237 2901 2975  
infoEU@hepergroup.com

We reserve the right to change specifications  
without prior written notice. Edition: 03.05.2024.  
For current version visit [heperlighting.com](http://heperlighting.com). All  
flux (±%7 tolerance) and power values (±%10  
tolerance) are derived following appropriate IES,  
CIE, and applicable standards.

## Poles (To be ordered separately)

### Conical aluminum poles with flange plate



| Product code | Height           | Diameter / Dimensions | Spigot diameter |
|--------------|------------------|-----------------------|-----------------|
| PAFK.D114    | 3m, 4m, 5m m     | Ø114mm                | Ø60mm, Ø76mm mm |
| PAFK.D122    | 4m, 5m, 6m m     | Ø122mm                | Ø60mm, Ø76mm mm |
| PAFK.D148    | 6m, 7m, 8m m     | Ø148mm                | Ø60mm, Ø76mm mm |
| PAFK.D165    | 6m, 7m, 8m, 9m m | Ø165mm                | Ø76mm, Ø90mm mm |
| PAFK.D180    | 10m, 8m, 9m m    | Ø180mm                | Ø76mm, Ø90mm mm |
| PAFK.D200    | 10m, 11m, 12m m  | Ø200mm                | Ø76mm, Ø90mm mm |

### Conical aluminum poles with embedded base



| Product code | Height           | Diameter / Dimensions | Spigot diameter |
|--------------|------------------|-----------------------|-----------------|
| PABK.D114    | 3m, 4m, 5m m     | Ø114mm                | Ø60mm, Ø76mm mm |
| PABK.D122    | 4m, 5m, 6m, 7m m | Ø122mm                | Ø60mm, Ø76mm mm |
| PABK.D148    | 6m, 7m, 8m m     | Ø148mm                | Ø60mm, Ø76mm mm |
| PABK.D165    | 6m, 7m, 8m, 9m m | Ø165mm                | Ø76mm, Ø90mm mm |
| PABK.D180    | 10m, 8m, 9m m    | Ø180mm                | Ø76mm, Ø90mm mm |
| PABK.D200    | 10m, 11m, 12m m  | Ø200mm                | Ø76mm, Ø90mm mm |

### Cylindrical aluminum poles with flange plate



| Product code | Height           | Diameter / Dimensions | Spigot diameter |
|--------------|------------------|-----------------------|-----------------|
| PAFC.D114    | 3m, 4m, 5m m     | Ø114mm                | Ø114mm mm       |
| PAFC.D122    | 3m, 4m, 5m, 6m m | Ø122mm                | Ø122mm mm       |
| PAFC.D148    | 6m, 7m, 8m m     | Ø148mm                | Ø148mm mm       |
| PAFC.D165    | 6m, 7m, 8m, 9m m | Ø165mm                | Ø165mm mm       |

|              |  |      |  |          |  |
|--------------|--|------|--|----------|--|
| Project name |  | Type |  | Quantity |  |
| Date         |  | Note |  |          |  |

LL2028.861-EN-T4-500-827-\_\_-EN-C1-\_\_-\_\_-\_\_-\_\_-\_\_

| Light distribution                                                                    | Rated input power    | Colour temperature            | Control                  | Product colours                                           |
|---------------------------------------------------------------------------------------|----------------------|-------------------------------|--------------------------|-----------------------------------------------------------|
| <b>[T4]</b><br>Type IV, Asymmetric,<br>Forward throw -<br>117x64°                     | <b>[500]</b><br>25 W | <b>[827]</b><br>2700 K CRI 80 | <b>[ONOFF]</b><br>On/Off | <b>[HM1]</b><br>Black                                     |
|                                                                                       | <b>[700]</b><br>35 W | <b>[830]</b><br>3000 K CRI 80 | <b>[DALI]</b><br>DALI    | <b>[HM2]</b><br>Dark grey                                 |
| <b>[P4]</b><br>Special pedestrian<br>road distribution-right<br>side traffic - 20x78° | <b>[350]</b><br>18 W | <b>[740]</b><br>4000 K CRI 70 | <b>[AUTO]</b><br>AutoDIM | <b>[HM3]</b><br>Anthracite grey                           |
| <b>[T1]</b><br>Type I, Asymmetric,<br>Side throw - 111x48°                            |                      | <b>[840]</b><br>4000 K CRI 80 | <b>[STEP]</b><br>StepDIM | <b>[HM4]</b><br>Light grey                                |
| <b>[T2]</b><br>Type II, Asymmetric,<br>Side throw - 133x48°                           |                      |                               |                          | <b>[HM5]</b><br>White                                     |
| <b>[T2]</b><br>Type II, Asymmetric,<br>Side throw - 149x54°                           |                      |                               |                          | <b>[HM6]</b><br>Bronze                                    |
| <b>[T3]</b><br>Type III, Asymmetric,<br>Side throw - 143x63°                          |                      |                               |                          | <b>[CC]</b><br>Custom colour (Please<br>specify RAL code) |
| <b>[T5]</b><br>Type V, Symmetric -<br>117°                                            |                      |                               |                          |                                                           |
| Extras                                                                                |                      |                               |                          |                                                           |

|                                                              |
|--------------------------------------------------------------|
| <b>External surge protection</b>                             |
| <b>[SP10]</b><br>10 kV                                       |
| <b>Light output</b>                                          |
| <b>[BS]</b><br>Backlight Shield                              |
| <b>[CLO]</b><br>Constant light output                        |
| <b>[VS]</b><br>Visor for RHINO                               |
| <b>Mounting options</b>                                      |
| <b>[DMBA]</b><br>Double side-mount bracket                   |
| <b>[SMBA]</b><br>Side-mount bracket allowing +/-45° rotation |
| <b>[TMBA]</b><br>Top-mount bracket                           |
| <b>Consult the factory</b>                                   |
| <b>[UNI]</b><br>120-277V 50/60Hz                             |
| <b>Luminaire body options</b>                                |
| <b>[DPC]</b><br>Double powder coating                        |