

# VESTA L 8 LED

CE UK CA IK05 IP65




LB6021.500-EN-SLFB-350-830-ONOFF-EN-C1



PHASED-  
OUT

Ø200 mm  
7 7/8"

900 mm  
35 7/16"



[SLFB]

Special linear,  
Forward throw

## Variant

|                        |               |
|------------------------|---------------|
| Light distribution     | [SLFB] 85x90° |
| Delivered lumens flux  | 740 lm        |
| Rated input power      | 10 W          |
| Colour temperature     | 3000 K CRI 80 |
| Luminaire efficacy     | 74 lm/W       |
| Lamp                   | 8 LED         |
| MacAdam Ellipse        | 3 SDCM        |
| Lifetime L90B50 (hour) | >145,000      |
| Lifetime L80B50 (hour) | >145,000      |

## Options


## Technical information

|                         |                                                                           |
|-------------------------|---------------------------------------------------------------------------|
| Housing                 | Corrosion resistant, extruded, marine grade aluminum housing              |
| Finishing               | Chromate conversion pretreatment followed by electrostatic powder coating |
| Fasteners               | Stainless steel (AISI 304 / EN 1.4301 grade)                              |
| Lens / Reflector        | PMMA lens with high optical efficiency                                    |
| Glass / Diffusor        | Tempered safety glass                                                     |
| Impact protection       | IK05                                                                      |
| Ingress protection      | IP65                                                                      |
| Input voltage           | 220-240V 50/60Hz                                                          |
| Insulation class        | Class I                                                                   |
| Weight                  | 8.52 kg                                                                   |
| LED module              | High power LEDs on metal-core PCB                                         |
| Driver                  | Internal LED driver                                                       |
| Driver surge protection | 1/1 kV                                                                    |
| Power factor            | > 0.60                                                                    |
| Through wiring          | Single cable entry                                                        |
| Operating temperature   | -40...50°C                                                                |
| Cable                   | 0.5 m of flexible cable                                                   |

## Accessories (To be ordered separately)

---

### Anchorage



623J014

623J014

|                                                 |  |      |  |          |  |
|-------------------------------------------------|--|------|--|----------|--|
| Project name                                    |  | Type |  | Quantity |  |
| Date                                            |  | Note |  |          |  |
| LB6021.500-EN-SLFB-350-830-ONOFF-EN-C1-__-__-__ |  |      |  |          |  |

| Light distribution                                            | Rated input power                                        | Colour temperature            | Control                  | Product colours                                           |                                                                                     |
|---------------------------------------------------------------|----------------------------------------------------------|-------------------------------|--------------------------|-----------------------------------------------------------|-------------------------------------------------------------------------------------|
| <b>[SLFB]</b><br>Special linear,<br>Forward throw -<br>85x90° | <b>[350]</b><br>10 W                                     | <b>[830]</b><br>3000 K CRI 80 | <b>[ONOFF]</b><br>On/Off | <b>[HM1]</b><br>Black                                     |  |
|                                                               |                                                          | <b>[740]</b><br>4000 K CRI 70 |                          | <b>[HM2]</b><br>Dark grey                                 |  |
|                                                               |                                                          |                               |                          | <b>[HM3]</b><br>Anthracite grey                           |  |
|                                                               |                                                          |                               |                          | <b>[HM4]</b><br>Light grey                                |  |
|                                                               |                                                          |                               |                          | <b>[HM5]</b><br>White                                     |  |
|                                                               |                                                          |                               |                          | <b>[HM6]</b><br>Bronze                                    |  |
|                                                               |                                                          |                               |                          | <b>[CC]</b><br>Custom colour (Please<br>specify RAL code) |  |
| <b>Extras</b>                                                 | <b>Accessories (<i>To be<br/>ordered separately</i>)</b> |                               |                          |                                                           |                                                                                     |
| <b>Consult the factory</b>                                    | <b>Anchorage</b>                                         |                               |                          |                                                           |                                                                                     |
| <b>[UNI]</b><br>120-277V 50/60Hz                              | <b>[623J014]</b><br>623J014                              |                               |                          |                                                           |                                                                                     |
| <b>Luminaire body<br/>options</b>                             |                                                          |                               |                          |                                                           |                                                                                     |
| <b>[DPC]</b><br>Double powder<br>coating                      |                                                          |                               |                          |                                                           |                                                                                     |