




LB6021.500-US-SLFB-350-740-ONOFF-UNI-C1



PHASED-
OUT

Ø200 mm
7 7/8"

900 mm
35 7/16"



[SLFB]

Special linear,
Forward throw

Variant

Light distribution	[SLFB] 85x90°
Delivered lumens flux	800 lm
Rated input power	10 W
Colour temperature	4000 K CRI 70
Luminaire efficacy	80 lm/W
Lamp	8 LED
MacAdam Ellipse	3 SDCM
Lifetime L90B50 (hour)	>145,000
Lifetime L80B50 (hour)	>145,000


Options

Technical information

Housing	Corrosion resistant, extruded, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Lens / Reflector	PMMA lens with high optical efficiency
Glass / Diffusor	Tempered safety glass
Impact protection	IK05
Ingress protection	IP65
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Weight	18.7 lbs
LED module	High power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	3/3 kV
Power factor	> 0.40
Through wiring	Single cable entry
Operating temperature	-40...50°C
Cable	0.5 m of flexible cable

Accessories (To be ordered separately)








Anchorage



623J014

623J014

Project name		Type		Quantity	
Date		Note			
LB6021.500-US-SLFB-350-740-ONOFF-UNI-C1-__-__					

Light distribution	Rated input power	Colour temperature	Control	Product colours	
[SLFB] Special linear, Forward throw - 85x90°	[350] 10 W	[740] 4000 K CRI 70	[ONOFF] On/Off	[HM1] Black	
		[830] 3000 K CRI 80		[HM2] Dark grey	
				[HM3] Anthracite grey	
				[HM4] Light grey	
				[HM5] White	
				[HM6] Bronze	
				[CC] Custom colour (Please specify RAL code)	
Extras	Accessories (<i>To be ordered separately</i>)				
Luminaire body options	Anchorage				
	[623J014] 623J014				
[DPC] Double powder coating					