





LB6042.545-US-SLFB-350-830-ONOFF-UNI-C1



[SLFB]

Special linear,  
Forward throw

## Variant

Light distribution	[SLFB] 120x47°
Delivered lumens flux	69 lm
Rated input power	3 W
Colour temperature	3000 K CRI 80
Luminaire efficacy	23 lm/W
Lamp	1 LED
MacAdam Ellipse	3 SDCM
BUG rating	B0-U0-G0
Lifetime L90B50 (hour)	>102,000
Lifetime L80B50 (hour)	>102,000

## Options


## Technical information

Mounting	Surface mountable
Housing	Corrosion resistant, extruded, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Lens / Reflector	High reflectance aluminium coating, multifaceted micro reflector
Glass / Diffusor	Tempered safety glass
Impact protection	IK05
Ingress protection	IP65
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Weight	7.7 lbs
LED module	High power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	3/3 kV
Power factor	> 0.40
Through wiring	Single cable entry
Operating temperature	-25...50°C
Cable	0.5 m of flexible cable

## Accessories (To be ordered separately)

---








### Anchorage



**629J014**

629J014

Project name		Type		Quantity	
Date		Note			
LB6042.545-US-SLFB-350-830-ONOFF-UNI-C1-__-__-__					

Light distribution	Rated input power	Colour temperature	Control	Product colours	
<b>[SLFB]</b> Special linear, Forward throw - 120x47°	<b>[350]</b> 3 W	<b>[830]</b> 3000 K CRI 80	<b>[ONOFF]</b> On/Off	<b>[HM1]</b> Black	
		<b>[827]</b> 2700 K CRI 80		<b>[HM2]</b> Dark grey	
		<b>[740]</b> 4000 K CRI 70		<b>[HM3]</b> Anthracite grey	
		<b>[840]</b> 4000 K CRI 80		<b>[HM4]</b> Light grey	
				<b>[HM5]</b> White	
				<b>[HM6]</b> Bronze	
				<b>[CC]</b> Custom colour (Please specify RAL code)	
<b>Height</b>	<b>Extras</b>	<b>Accessories</b> ( <i>To be ordered separately</i> )			
<b>[H0.45]</b> 45cm  <b>[HC]</b>	<b>Luminaire body options</b>	<b>Anchorage</b>			
	<b>[DPC]</b> Double powder coating	<b>[629J014]</b> 629J014			