




ZETA 4 Dyno

CE UK CA IK08 IP67



LR9012.582-EN-WW-350-740-EN-C1-SS



[WW]
Wall-wash

Variant

Light distribution	[WW] 49x33°
Delivered lumens flux	930 lm
Rated input power	10 W
Colour temperature	4000 K CRI 70
Luminaire efficacy	93 lm/W
Lamp	4 LED
MacAdam Ellipse	3 SDCM
Lifetime L90B50 (hour)	>42,000
Lifetime L80B50 (hour)	>42,000


Options

Technical information

Mounting	Ground recessed mountable
Housing	Corrosion resistant stainless steel housing (AISI 316L / EN 1.4571 grade)
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	High reflectance aluminium coating, multifaceted micro reflector
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP67
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	2.77 kg
LED module	High power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge protection	1/1 kV
Power factor	> 0.90
Through wiring	Single cable entry
Operating temperature	-30...50°C
Cable	0.3 m of rubber-sheathed cable

Accessories (Included)

Mounting accessories



**Aluminium case
for ZETA 4 Dyno /
MOLTO 2 Hybrid**

007500582

Accessories (To be ordered separately)


Mounting accessories



**Case removing
vacuum**

160404012


Mounting accessories



**Connector set - 5-
pole**

141407400

Mounting accessories



Junction Box

141901135

Project name		Type		Quantity	
Date		Note			
LR9012.582-EN-WW-350-740-__-EN-C1-SS					

Light distribution	Rated input power	Colour temperature	Control	Product colours
[WW] Wall-wash - 49x33°	[350] 10 W	[740] 4000 K CRI 70	[ONOFF] On/Off	[SS] Stainless steel 
		[827] 2700 K CRI 80 [830] 3000 K CRI 80 [840] 4000 K CRI 80	[DALI] DALI	
Accessories (Included)	Accessories (To be ordered separately)			
Mounting accessories	Mounting accessories			
[007500582] Aluminium case for ZETA 4 Dyno / MOLTO 2 Hybrid	[160404012] Case removing vacuum [141407400] Connector set - 5-pole [141901135] Junction Box			