

# ZETA 4 Dyno


СЕ ЦКА ІКОВ ІР67 →



## LR9012.582-EN-WW-350-740-EN-C1-SS









Wall-wash

### Variant

Light distribution	[WW] 49x33°
Delivered lumens flux	930 lm
Rated input power	10 W
Colour temperature	4000 K CRI 70
Luminaire efficacy	93 lm/W
Lamp	4 LED
MacAdam Ellipse	3 SDCM
Lifetime L90B50 (hour)	>42,000
Lifetime L80B50 (hour)	>42,000

### Options

Cable

### **Technical information**

Mounting	Ground recessed mountable
Housing	Corrosion resistant stainless steel housing (AISI
	316L / EN 1.4571 grade)
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	
Lens / Reflector	High reflectance aluminium coating,
el ( 510	multifaceted micro reflector
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP67
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	2.77 kg
LED module	High power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	1/1 kV
protection	
Power factor	> 0.90
Through wiring	Single cable entry
Operating	-3050°C
temperature	

0.3 m of rubber-sheated cable

HPR Pazarlama A.Ş.

Başkent OSB 22. Cd. No: 2, Malıköy, Temelli, Sincan, 06909 Ankara, Turkey +90 312 267 54 30 info@hepergroup.com

#### HEPER Europe GmbH

Ahornweg 5a, 58675 Hemer, Germany +49 237 2901 2975 infoEU@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 01.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

1/3

# Accessories (Included)

# Accessories (To be ordered separately)

#### Mounting accessories



Aluminium case for ZETA 4 Dyno / MOLTO 2 Hybrid

007500582

### Mounting accessories Mounting

Mounting accessories Mounting accessories





Case removing Connector set - 5pole 160404012 141407400 000

Junction Box 141901135

HPR Pazarlama A.Ş. Başkent OSB 22. Cd. No: 2, Malıköy, Temelli, Sincan, 06909 Ankara, Turkey +90 312 267 54 30 info@hepergroup.com

#### HEPER Europe GmbH

Ahornweg 5a, 58675 Hemer, Germany +49 237 2901 2975 infoEU@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 01.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

2/3

Project na	me			Туре	Quantity		
Date			Note				
LR9012.	582-EN-W	/W-350-7	40EN	-C1-SS			

<b>350]</b> 10 W	[740] 4000 K CRI 70 [827] 2700 K CRI 80 [830] 3000 K CRI 80 [840] 4000 K CRI 80	<b>[ONOFF]</b> On/Off <b>[DALI]</b> DALI	[SS] Stainless steel
	2700 K CRI 80 [830] 3000 K CRI 80 [840]	1	
	3000 K CRI 80 [840]		
Accessories (To be			
Mounting accessories			
[ <b>160404012]</b> Case removing vacuum			
[ <b>141407400]</b> Connector set - 5-pole			
[ <b>141901135]</b> unction Box			
2 N [1 ] ] ] ]	rdered separately) lounting ccessories lo0404012] ase removing acuum l41407400] onnector set - 5-pole l41901135]	rdered separately)         lounting         ccessories         60404012]         ase removing         acuum         41407400]         onnector set - 5-pole         41901135]	rdered separately) lounting ccessories l60404012] ase removing acuum l41407400] onnector set - 5-pole l41901135]

### HEPER Europe GmbH

Ahornweg 5a, 58675 Hemer, Germany +49 237 2901 2975 infoEU@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 01.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.