
VESTA S L 8 LED

heper, t

LB6045.500-EN-SLFB-350-740-ONOFF







[SLFB]Special linear,
Forward throw

Configuration

Light distribution [SLFB] 85x90° **Delivered lumens flux** 800 lm Rated input power 10 W **Color temperature** 4000 K CRI 70 **Luminaire efficacy** 80 lm/W 8 LED Lamp **Color Deviation** 3 SDCM Lifetime L90 (hour) >145,000 >145,000 Lifetime L80 (hour)

Options

Technical information

reemmean milotim	action :
Housing	Corrosion resistant, extruded, marine grade
	aluminum housing
Finishing	Chromate conversion pretreatment followed by
	electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Lens / Reflector	PMMA lens with high optical efficiency
Glass / Diffusor	Tempered safety glass
Impact protection	IK05
Ingress protection	IP65
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	5.61 kg

LED module High power LEDs on metal-core PCB

Driver Internal LED driver

Driver surge 1/1 kV **protection**

Power factor > 0.60
Through wiring Single power cord entry

Operating -40...50°C

temperature

Power cord 20" of outdoor use rated flexible power cord

1/3

heperlighting.com. All flux (\pm %7 tolerance) and power values (\pm %10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

Accessories (To be ordered separately)

Anchor bolts



629J014

629J014

Project na	me		Туре	Quantity	
Date		Note			

LB6045.500-EN-SLFB-350-740-ONOFF-__--_-

Light distribution	Rated input power	Color temperature	Control	Product colors
[SLFB] Special linear,	[350] 10 W	[740] 4000 K CRI 70	[ONOFF] On/Off	[HM1] Black
Forward throw - 85x90°		[830] 3000 K CRI 80		[HM2] Dark gray
				[HM3] Anthracite gray
				[HM4] Light gray
				[HM5] White
				[HM6] Bronze
				Custom color (Please specify RAL code)
Extras	Accessories (To be ordered separately)			
Consult the factory	Anchor bolts			
[UNI] 120-277V 50/60Hz	[629J014] 629J014			
Luminaire body options				
[DPC] Double powder coating				