

VESTA S L 8 LED


CE UK CA IK05 IP65



LB6045.500-EN-SLFB-350-830-ONOFF-EN-C1



PHASED-
OUT



[SLFB]

Special linear,
Forward throw

Variant

| | |
|------------------------|---------------|
| Light distribution | [SLFB] 85x90° |
| Delivered lumens flux | 740 lm |
| Rated input power | 10 W |
| Colour temperature | 3000 K CRI 80 |
| Luminaire efficacy | 74 lm/W |
| Lamp | 8 LED |
| MacAdam Ellipse | 3 SDCM |
| Lifetime L90B50 (hour) | >145,000 |
| Lifetime L80B50 (hour) | >145,000 |


Options

Technical information

| | |
|-------------------------|---------------------------------------------------------------------------|
| Housing | Corrosion resistant, extruded, marine grade aluminum housing |
| Finishing | Chromate conversion pretreatment followed by electrostatic powder coating |
| Fasteners | Stainless steel (AISI 304 / EN 1.4301 grade) |
| Lens / Reflector | PMMA lens with high optical efficiency |
| Glass / Diffusor | Tempered safety glass |
| Impact protection | IK05 |
| Ingress protection | IP65 |
| Input voltage | 220-240V 50/60Hz |
| Insulation class | Class I |
| Weight | 5.61 kg |
| LED module | High power LEDs on metal-core PCB |
| Driver | Internal LED driver |
| Driver surge protection | 1/1 kV |
| Power factor | > 0.60 |
| Through wiring | Single cable entry |
| Operating temperature | -40...50°C |
| Cable | 0.5 m of flexible cable |

Accessories (To be ordered separately)








Anchorage



629J014

629J014

| | | | | | |
|-------------------------------------------------|--|------|--|----------|--|
| Project name | | Type | | Quantity | |
| Date | | Note | | | |
| LB6045.500-EN-SLFB-350-830-ONOFF-EN-C1-__-__-__ | | | | | |

| Light distribution | Rated input power | Colour temperature | Control | Product colours | |
|---------------------------------------------------------------|----------------------------------------------------------|-------------------------------|--------------------------|-----------------------------------------------------------|-------------------------------------------------------------------------------------|
| [SLFB] Special linear, Forward throw - 85x90° | [350] 10 W | [830] 3000 K CRI 80 | [ONOFF] On/Off | [HM1] Black |  |
| | | [740] 4000 K CRI 70 | | [HM2] Dark grey |  |
| | | | | [HM3] Anthracite grey |  |
| | | | | [HM4] Light grey |  |
| | | | | [HM5] White |  |
| | | | | [HM6] Bronze |  |
| | | | | [CC] Custom colour (Please specify RAL code) |  |
| Extras | Accessories (<i>To be ordered separately</i>) | | | | |
| Consult the factory | Anchorage | | | | |
| [UNI] 120-277V 50/60Hz | [629J014] 629J014 | | | | |
| Luminaire body options | | | | | |
| [DPC] Double powder coating | | | | | |