

TILA S AFX 3 Module

LL2030.863-EN-T5-350-827-ONOFF









Type V

Configuration

Light distribution [T5] 117° Delivered lumens flux 6170 lm Rated input power 50 W **Color temperature** 2700 K CRI 80 Luminaire efficacy 121 lm/W Lamp 48 I FD **Color Deviation** 3 SDCM B2-U0-G0 **BUG** rating Lifetime L90 (hour) >102,000 Lifetime L80 (hour) >102,000

Options

Technical information

Mounting Direct pole or side bracket mountable. Tenon:

Ø2 1/4" x 4"

Housing Corrosion resistant, marine grade aluminum

housing

Finishing Chromate conversion pretreatment followed by

electrostatic powder coating

Fasteners Stainless steel (AISI 304 / EN 1.4301 grade) Gasket

Liquid silicone

Lens / Reflector PMMA lens with high optical efficiency Glass / Diffusor

Tempered safety glass **IK08**

Impact protection

Ingress protection IP66

Input voltage 220-240V 50/60Hz

Insulation class Class I

Weight 27.42 kg (5 m), 30.57 kg (6 m)

LED module High power LEDs on metal-core PCB

Driver Internal LED driver

Driver surge 10/6 kV

protection

Power factor > 0.95

Through wiring Single power cord entry

Operating -40...50°C

temperature

20" of outdoor use rated flexible power cord Power cord

Packing box 40*35*7 cm

dimensions

Poles are supplied with flange plate. Flange Pole detail


cover and anchorage can be ordered separately.

Embedded base is optional

Notes QUICK SHIP: Some variants will be delivered

faster. Please consult the factory.

Product specific poles with base plate



Project na	me		Туре	Quantity	
Date		Note			

LL2030.863-EN-T5-350-827-ONOFF-__--_--

Light distribution	Rated input power	Color temperature	Control	Product colors
[T5] Type V - 117°	[350] 50 W	[827] 2700 K CRI 80	[ONOFF] On/Off	[HM1] Black
[P4] Pedestrian crosswalk distribution - 20x78°	[500] 72 W	[830] 3000 K CRI 80		[HM2] Dark gray
[T1] Type I - 111x48°	[700] 100 W	[740] 4000 K CRI 70 [840] 4000 K CRI 80		[HM3] Anthracite gray
[T2] Type II - 133x48°				[HM4] Light gray
[T2] Type II - 149x54°				[HM5] White
[T3] Type III - 143x63°				[HM6] Bronze
[T4] Type IV - 117x64°				Custom color (Please specify RAL code)
Height	Extras			
[H5]	Consult the factory			
16.4' [H6]	[UNI] 120-277V 50/60Hz			
19.7' [HC]	Luminaire body options			
	[DPC] Double powder coating			