
# NORMA S

СЕ ЦКА 1К05 1Р65 🔔



## LB6054.006-EN-SYM-4L-940-ONOFF-EN-C1







**[SYM-4L]** Symmetric, Special effect: 4 lines



Light distribution	[SYM-4L]
Delivered lumens flux	410 lm
Rated input power	7.5 W
Colour temperature	4000 K CRI 90
Luminaire efficacy	55 lm/W
Lamp	1 LAMP
MacAdam Ellipse	5 SDCM
BUG rating	B0-U1-G0

## Options

## Technical information

Housing	Corrosion resistant, extruded, marine grade
Finishing	aluminum housing Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Liquid silicone
Glass / Diffusor	Tempered safety glass
Impact protection	IK05
Ingress protection	IP65
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	3.5 kg
Driver	Internal LED driver
Power factor	> 0.80
Through wiring	Single cable entry
Cable	0.5 m of flexible cable
Notes	This product is supplied without a bulb as
	standard. The shown lighting distribution and
	performance are indicative but can change
	depending on the bulb. Please consult the
	factory for bulb options and availability.

HPR Pazarlama A.Ş. Başkent OSB 22. Cd. No: 2, Malıköy, Temelli, Sincan, 06909 Ankara, Turkey +90 312 267 54 30 info@hepergroup.com

#### HEPER Europe GmbH

Ahornweg 5a, 58675 Hemer, Germany +49 237 2901 2975 infoEU@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 04.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

# Accessories (To be ordered separately)



6281001

HPR Pazarlama A.Ş. Başkent OSB 22. Cd. No: 2, Malıköy, Temelli, Sincan, 06909 Ankara, Turkey +90 312 267 54 30 info@hepergroup.com

#### HEPER Europe GmbH

Ahornweg 5a, 58675 Hemer, Germany +49 237 2901 2975 infoEU@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 04.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

2/3

Project na	me				Туре	Quantity	
Date			Note				
LB6054.	006-EN-S	YM-4L-94	0-ONOFI	-EN-C1			

Light distribution	Rated input power	Colour temperature	Control	Product colours
<b>[SYM-4L]</b> Symmetric, Special	[] 7.5 W	<b>[940]</b> 4000 K CRI 90	[ONOFF] On/Off	[HM1] Black
effect: 4 lines		<b>[930]</b> 3000 K CRI 90		[HM2] Dark grey
				[HM3] Anthracite grey
				[HM4] Light grey
				[HM5] White
				[HM6] Bronze
				[ <b>CC</b> ] Specify RAL code)
Extras	Accessories (To be ordered separately)			
Consult the factory	Anchorages			
<b>[UNI]</b> 120-277V 50/60Hz	<b>[6281001]</b> 6281001			
Luminaire body options				
<b>[DPC]</b> Double powder coating				

HPR Pazarlama A.Ş. Başkent OSB 22. Cd. No: 2, Malıköy, Temelli, Sincan, 06909 Ankara, Turkey +90 312 267 54 30

info@hepergroup.com

HEPER Europe GmbH

Ahornweg 5a, 58675 Hemer, Germany +49 237 2901 2975 infoEU@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 04.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.