



# D-LIGHT AFX 3 Module



LL2023.863-EN-T1-700-740



[T1]  
Type I

## Configuration

|                       |               |
|-----------------------|---------------|
| Light distribution    | [T1] 111x48°  |
| Delivered lumens flux | 13120 lm      |
| Rated input power     | 100 W         |
| Color temperature     | 4000 K CRI 70 |
| Luminaire efficacy    | 127 lm/W      |
| Lamp                  | 48 LED        |
| Color Deviation       | 4 SDCM        |
| BUG rating            | B3-U1-G2      |
| Lifetime L90 (hour)   | >102,000      |
| Lifetime L80 (hour)   | >102,000      |

## Options

## Technical information

|                             |                                                                                                |
|-----------------------------|------------------------------------------------------------------------------------------------|
| Mounting                    | Direct pole or side bracket mountable. Tenon:<br>Ø2 1/4" x 4"                                  |
| Tilt angle                  | +15°/-15°                                                                                      |
| Housing                     | Corrosion resistant, die-cast, marine grade<br>aluminum housing                                |
| Finishing                   | Chromate conversion pretreatment followed by<br>electrostatic powder coating                   |
| Fasteners                   | Stainless steel (AISI 304 / EN 1.4301 grade)                                                   |
| Gasket                      | EPDM gasket (Shore A 20-25)                                                                    |
| Lens / Reflector            | PMMA lens with high optical efficiency                                                         |
| Glass / Diffusor            | Tempered safety glass                                                                          |
| Impact protection           | IK08                                                                                           |
| Ingress protection          | IP66                                                                                           |
| Input voltage               | 220-240V 50/60Hz                                                                               |
| Insulation class            | Class I                                                                                        |
| Wind catching area<br>(EPA) | 0.08 m <sup>2</sup>                                                                            |
| Weight                      | 8.68 kg                                                                                        |
| LED module                  | High power LEDs on metal-core PCB                                                              |
| Driver                      | Internal LED driver                                                                            |
| Driver surge<br>protection  | 10/6 kV                                                                                        |
| Power factor                | > 0.98                                                                                         |
| Through wiring              | Single power cord entry                                                                        |
| Operating<br>temperature    | -40...50°C                                                                                     |
| Power cord                  | 20" of outdoor use rated flexible power cord                                                   |
| Packing box<br>dimensions   | 100*20*16 cm                                                                                   |
| Pole detail                 | Poles are supplied with flange plate. Flange<br>cover and anchorage can be ordered separately. |

## Notes

Embedded base is optional  
This product can be supplied with Insulation  
class (Class II) upon request. Please contact  
factory.

Poles (To be ordered separately)

Round tapered aluminum poles with base plate

|  | Product code | Height                     | Diameter / Dimensions | Spigot / End diameter |
|-----------------------------------------------------------------------------------|--------------|----------------------------|-----------------------|-----------------------|
|                                                                                   | PAFK.D114    | 10', 13.1', 16.4'          | Ø4 1/2"               | Ø2 3/8", Ø3"          |
|                                                                                   | PAFK.D122    | 13.1', 16.4', 19.7'        | Ø5"                   | Ø2 3/8", Ø3"          |
|                                                                                   | PAFK.D148    | 19.7', 23.0', 26.2'        | Ø6"                   | Ø2 3/8", Ø3"          |
|                                                                                   | PAFK.D165    | 19.7', 23.0', 26.2', 29.5' | Ø6 1/2"               | Ø3 1/2", Ø3"          |
|                                                                                   | PAFK.D180    | 26.2', 29.5', 32.8'        | Ø7"                   | Ø3 1/2", Ø3"          |
|                                                                                   | PAFK.D200    | 32.8', 36.1', 39.4'        | Ø7 7/8"               | Ø3 1/2", Ø3"          |

Round tapered aluminum poles (direct burial)


|  | Product code | Height                     | Diameter / Dimensions | Spigot / End diameter |
|-----------------------------------------------------------------------------------|--------------|----------------------------|-----------------------|-----------------------|
|                                                                                   | PABK.D114    | 10', 13.1', 16.4'          | Ø4 1/2"               | Ø2 3/8", Ø3"          |
|                                                                                   | PABK.D122    | 13.1', 16.4', 19.7', 23.0' | Ø5"                   | Ø2 3/8", Ø3"          |
|                                                                                   | PABK.D148    | 19.7', 23.0', 26.2'        | Ø6"                   | Ø2 3/8", Ø3"          |
|                                                                                   | PABK.D165    | 19.7', 23.0', 26.2', 29.5' | Ø6 1/2"               | Ø3 1/2", Ø3"          |
|                                                                                   | PABK.D180    | 26.2', 29.5', 32.8'        | Ø7"                   | Ø3 1/2", Ø3"          |
|                                                                                   | PABK.D200    | 32.8', 36.1', 39.4'        | Ø7 7/8"               | Ø3 1/2", Ø3"          |

Round cylindrical aluminum poles with base plate

|  | Product code | Height                     | Diameter / Dimensions | Spigot / End diameter |
|-----------------------------------------------------------------------------------|--------------|----------------------------|-----------------------|-----------------------|
|                                                                                   | PAFC.D114    | 10', 13.1', 16.4'          | Ø4 1/2"               | Ø4 1/2"               |
|                                                                                   | PAFC.D122    | 10', 13.1', 16.4', 19.7'   | Ø5"                   | Ø4 51/64"             |
|                                                                                   | PAFC.D148    | 19.7', 23.0', 26.2'        | Ø6"                   | Ø5 7/8"               |
|                                                                                   | PAFC.D165    | 19.7', 23.0', 26.2', 29.5' | Ø6 1/2"               | Ø6 1/2"               |

Accessories (To be ordered separately)

Mounting accessories



Wall mounting bracket

B6A.03.03.01001.0220

|              |  |      |  |      |  |          |  |
|--------------|--|------|--|------|--|----------|--|
| Project name |  |      |  | Type |  | Quantity |  |
| Date         |  | Note |  |      |  |          |  |

LL2023.863-EN-T1-700-740-

| Light distribution                                                                                                                                                                                                                                                                                                                                                                                                                         | Rated input power                                                                                                                          | Color temperature                                                                                                                                                    | Control                                                                                                                                                                                              | Product colors                                                                                                                                                                                                                  |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <div> <div>[T1]</div> <div>Type I - 111x48°</div> </div> <div> <div>[P4]</div> <div>Pedestrian crosswalk distribution - 20x78°</div> </div> <div> <div>[T2]</div> <div>Type II - 133x48°</div> </div> <div> <div>[T2]</div> <div>Type II - 149x54°</div> </div> <div> <div>[T3]</div> <div>Type III - 143x63°</div> </div> <div> <div>[T4]</div> <div>Type IV - 117x64°</div> </div> <div> <div>[T5]</div> <div>Type V - 117°</div> </div> | <div> <div>[700]</div> <div>100 W</div> </div> <div> <div>[350]</div> <div>50 W</div> </div> <div> <div>[500]</div> <div>72 W</div> </div> | <div> <div>[740]</div> <div>4000 K CRI 70</div> </div> <div> <div>[730]</div> <div>3000 K CRI 70</div> </div> <div> <div>[830]</div> <div>3000 K CRI 80</div> </div> | <div> <div>[ONOFF]</div> <div>On/Off</div> </div> <div> <div>[DALI]</div> <div>DALI</div> </div> <div> <div>[AUTO]</div> <div>AutoDIM</div> </div> <div> <div>[STEP]</div> <div>StepDIM</div> </div> | <div> <div>[HM3]</div> <div>Anthracite gray</div> <div></div> </div> <div> <div>[HM4]</div> <div>Light gray</div> <div></div> </div> <div> <div>[CC]</div> <div>Custom color (Please specify RAL code)</div> <div></div> </div> |
| Extras                                                                                                                                                                                                                                                                                                                                                                                                                                     | Accessories ( <i>To be ordered separately</i> )                                                                                            |                                                                                                                                                                      |                                                                                                                                                                                                      |                                                                                                                                                                                                                                 |
| External surge protection                                                                                                                                                                                                                                                                                                                                                                                                                  | Mounting accessories                                                                                                                       |                                                                                                                                                                      |                                                                                                                                                                                                      |                                                                                                                                                                                                                                 |
| <div>[SP10]</div> <div>10 kV</div>                                                                                                                                                                                                                                                                                                                                                                                                         | <div>[B6A.03.03.01001.0220]</div> <div>Wall mounting bracket</div>                                                                         |                                                                                                                                                                      |                                                                                                                                                                                                      |                                                                                                                                                                                                                                 |
| Connectivity                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                                                                            |                                                                                                                                                                      |                                                                                                                                                                                                      |                                                                                                                                                                                                                                 |
| <div>[NM7]</div> <div>7 Pin NEMA socket</div>                                                                                                                                                                                                                                                                                                                                                                                              |                                                                                                                                            |                                                                                                                                                                      |                                                                                                                                                                                                      |                                                                                                                                                                                                                                 |
| Light output                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                                                                            |                                                                                                                                                                      |                                                                                                                                                                                                      |                                                                                                                                                                                                                                 |
| <div>[CLO]</div> <div>Constant light output</div>                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                            |                                                                                                                                                                      |                                                                                                                                                                                                      |                                                                                                                                                                                                                                 |
| Consult the factory                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                            |                                                                                                                                                                      |                                                                                                                                                                                                      |                                                                                                                                                                                                                                 |
| <div>[C2]</div> <div>Class II</div> <div>[UNI]</div> <div>120-277V 50/60Hz</div>                                                                                                                                                                                                                                                                                                                                                           |                                                                                                                                            |                                                                                                                                                                      |                                                                                                                                                                                                      |                                                                                                                                                                                                                                 |
| Luminaire body options                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                            |                                                                                                                                                                      |                                                                                                                                                                                                      |                                                                                                                                                                                                                                 |
| <div>[DPC]</div> <div>Double powder coating</div>                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                            |                                                                                                                                                                      |                                                                                                                                                                                                      |                                                                                                                                                                                                                                 |