

ZETA 4 Dyno


CE UK IKO8 IP67



LR9012.582-EN-WW-350-830-EN-C1-SS









Variant

Light distribution [WW] 49x33° **Delivered lumens flux** 818 lm Rated input power 10 W **Colour temperature** 3000 K CRI 80 **Luminaire efficacy** 81 lm/W 4 LED Lamp MacAdam Ellipse 3 SDCM Lifetime L90B50 (hour) >42,000 >42,000 Lifetime L80B50 (hour)

Options

Technical information

recrinical inform	ation
Mounting	Ground recessed mountable
Housing	Corrosion resistant stainless steel housing (AISI
	316L / EN 1.4571 grade)
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Silicone
Lens / Reflector	High reflectance aluminium coating,
	multifaceted micro reflector
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP67
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	2.77 kg
LED module	High power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	1/1 kV
protection	
Power factor	> 0.90
Through wiring	Single cable entry
Operating	-3050°C

temperature

Cable 0.3 m of rubber-sheated cable


Mounting accessories



Aluminium case for ZETA 4 Dyno / MOLTO 2 Hybrid

007500582

Mounting accessories



Mounting accessories Mounting accessories



Case removing vacuum

160404012



Connector set - 5pole

141407400



Junction Box

141901135

Project na	me		Туре	Quantity	
Date		Note			

LR9012.582-EN-WW-350-830-__--EN-C1-SS

Light distribution	Rated input power	Colour temperature	Control	Product colours
[WW] Wall-wash - 49x33°	[350] 10 W	[830] 3000 K CRI 80	[ONOFF] On/Off	[SS] Stainless steel
		[827] 2700 K CRI 80	[DALI] DALI	
		[740] 4000 K CRI 70		
		[840] 4000 K CRI 80		
Accessories (Included)	Accessories (To be ordered separately)			
Mounting accessories	Mounting accessories			
[007500582] Aluminium case for ZETA 4 Dyno / MOLTO 2 Hybrid	[160404012] Case removing vacuum			
	[141407400] Connector set - 5-pole			
	[141901135] Junction Box			