


ZETA 4 Dyno

heper, t

LR9012.582-EN-WW-350-830-SS









Configuration

Light distribution [WW] 49x33° Delivered lumens flux 818 lm Rated input power 10 W **Color temperature** 3000 K CRI 80 81 lm/W **Luminaire efficacy** 4 LED Lamp **Color Deviation** 3 SDCM Lifetime L90 (hour) >42,000 >42,000 Lifetime L80 (hour)

Options

Technical information

Mounting Ground recessed mountable Housing Corrosion resistant stainless steel housing (AISI 316L / EN 1.4571 grade) **Fasteners** Stainless steel (AISI 304 / EN 1.4301 grade) Gasket Silicone Lens / Reflector High reflectance aluminium coating, multifaceted micro reflector Glass / Diffusor Tempered safety glass Impact protection IK08 IP67 Ingress protection Input voltage 220-240V 50/60Hz **Insulation class** Class I Weight 2.77 kg LED module High power LEDs on metal-core PCB Internal LED driver Driver 1/1 kV **Driver surge** protection **Power factor** > 0.90

Through wiringSingle power cord entry **Operating**-30...50°C

temperature

Power cord 12" of rubber-sheated power cord

and applicable standards.

Mounting accessories



Aluminium case for ZETA 4 Dyno / MOLTO 2 Hybrid

007500582

Mounting accessories Mounting accessories Mounting accessories



Case removing vacuum

160404012

Connector set - 5pole

141407400



Junction Box

141901135

Project name					Туре	Quantity	
Date			Note				

LR9012.582-EN-WW-350-830-__--SS

Light distribution	Rated input power	Color temperature	Control	Product colors
[ww] Wall-wash - 49x33°	[350] 10 W	[830] 3000 K CRI 80	[ONOFF] On/Off	[SS] Stainless steel
		[827] 2700 K CRI 80	[DALI] DALI	
		[740] 4000 K CRI 70		
		[840] 4000 K CRI 80		
Accessories (Included)	Accessories (To be ordered separately)			
Mounting accessories	Mounting accessories			
[007500582] Aluminium case for ZETA 4 Dyno / MOLTO	[160404012] Case removing vacuum			
2 Hybrid	[141407400] Connector set - 5-pole			
	[141901135] Junction Box			