

DOMINO W AFX 2 Module

heper to hep

LW7031.862-EN-T3-700-830









[T3] Type III

Configuration

Light distribution [T3] 143x63° Delivered lumens flux 6980 lm Rated input power 67 W **Color temperature** 3000 K CRI 80 **Luminaire efficacy** 104 lm/W Lamp 32 LED **Color Deviation** 3 SDCM B2-U1-G1 **BUG** rating Lifetime L90 (hour) >102,000 Lifetime L80 (hour) >102,000

Options

Technical information

MountingSurface or wall mountableHousingCorrosion resistant, marine grade aluminum
housingFinishingChromate conversion pretreatment followed by
electrostatic powder coatingFastenersStainless steel (AISI 304 / EN 1.4301 grade)

Gasket Liquid silicone
Lens / Reflector PMMA lens with high optical efficiency
Glass / Diffusor Tempered safety glass
Impact protection IK08
Ingress protection IP66
Input voltage 220-240V 50/60Hz

Insulation classClass IWeight7.75 kgLED moduleHigh power LEDs on metal-core PCB

Driver Internal LED driver **Driver surge** 10/6 kV

Driver surge 10/6 kV protection

Power factor> 0.95Through wiringSingle power cord entryOperating-40...50°C

temperature

Power cord8" of flexible power cordPacking box20*16*100 cm

dimensions

| Project name | | | | Туре | Quantity | |
|--------------|--|------|--|------|----------|--|
| Date | | Note | | | | |

LW7031.862-EN-T3-700-830-__--__-

| Light distribution | Rated input power | Color temperature | Control | Product colors | |
|----------------------------------------------|-----------------------|---------------------------------|-------------------------------|---------------------------------------------|--|
| [T3] Type III - 143x63° | [700] 67 W | [830] 3000 K CRI 80 | [ONOFF] On/Off | [HM1] Black | |
| [P4] Pedestrian crosswalk | [350] 34 W | [827] 2700 K CRI 80 | [DALI] DALI | [HM2] Dark gray | |
| distribution - 20x78° [T1] Type I - 111x48° | [500] 48 W | [740] 4000 K CRI 70 | [AUTO] AutoDIM [STEP] StepDIM | [HM3] Anthracite gray | |
| [T2] Type II - 133x48° | | [840] 4000 K CRI 80 | | [HM4] Light gray | |
| [T2] Type II - 149x54° | | | | [HM5] White | |
| [T4] Type IV - 117x64° | | | | [HM6] Bronze | |
| [T5] Type V - 117° | | | | [CC] Custom color (Please specify RAL code) | |

| Extr | as |
|------|----|
|------|----|

Light output

[BS]

Backlight Shield

Consult the factory

[UNI]

120-277V 50/60Hz

Luminaire body options

[DPC]

Double powder coating