

DOMINO W AFX 2 Module

heper t

LW7031.862-EN-T3-700-827









[T3] Type III

Configuration

Light distribution [T3] 143x63° Delivered lumens flux 6980 lm Rated input power 67 W **Color temperature** 2700 K CRI 80 **Luminaire efficacy** 104 lm/W Lamp 32 LED **Color Deviation** 3 SDCM B2-U1-G1 **BUG** rating Lifetime L90 (hour) >102,000 Lifetime L80 (hour) >102,000

Options

Technical information

MountingSurface or wall mountableHousingCorrosion resistant, marine grade aluminum
housingFinishingChromate conversion pretreatment followed by
electrostatic powder coatingFastenersStainless steel (AISI 304 / EN 1.4301 grade)

Gasket Liquid silicone
Lens / Reflector PMMA lens with high optical efficiency
Glass / Diffusor Tempered safety glass
Impact protection IK08
Ingress protection IP66
Input voltage 220-240V 50/60Hz

Insulation class Class I
Weight 7.75 kg

LED moduleHigh power LEDs on metal-core PCBDriverInternal LED driverDriver surge10/6 kVprotection10/6 kV

Power factor > 0.95
Through wiring Single power cord entry
Operating -40...50°C

Power cord 8" of flexible power cord
Packing box 20*16*100 cm

dimensions

temperature

Project name				Туре	Quantity	
Date		Note				

LW7031.862-EN-T3-700-827-__--_--

Light distribution	Rated input power	Color temperature	Control	Product colors
[T3] Type III - 143x63°	[700] 67 W	[827] 2700 K CRI 80	[ONOFF] On/Off	[HM1] Black
[P4] Pedestrian crosswalk	[350] 34 W	[830] 3000 K CRI 80	[DALI] DALI	[HM2] Dark gray
distribution - 20x78° [T1] Type I - 111x48°	[500] 48 W	[740] 4000 K CRI 70	[AUTO] AutoDIM [STEP] StepDIM	[HM3] Anthracite gray
[T2] Type II - 133x48°		[840] 4000 K CRI 80		[HM4] Light gray
[T2] Type II - 149x54°				[HM5] White
[T4] Type IV - 117x64°				[HM6] Bronze
[T5] Type V - 117°				[CC] Custom color (Please specify RAL code)

Extr	as
------	----

Light output

[BS]

Backlight Shield

Consult the factory

[UNI]

120-277V 50/60Hz

Luminaire body options

[DPC]

Double powder coating