
DOMINO W AFX 2 Module




LW7031.862-EN-T5-700-827





4 23/32"





Type V

Configuration

Delivered lumens flux7645 lmRated input power67 WColor temperature2700 K CRI 80Luminaire efficacy114 lm/WLamp32 LEDColor Deviation3 SDCMBUG ratingB3-U0-G0Lifetime L90 (hour)>102,000Lifetime L80 (hour)>102,000	Light distribution	[T5] 117°
Color temperature2700 K CRI 80Luminaire efficacy114 lm/WLamp32 LEDColor Deviation3 SDCMBUG ratingB3-U0-G0Lifetime L90 (hour)>102,000	Delivered lumens flux	7645 lm
Luminaire efficacy114 lm/WLamp32 LEDColor Deviation3 SDCMBUG ratingB3-U0-G0Lifetime L90 (hour)>102,000	Rated input power	67 W
Lamp32 LEDColor Deviation3 SDCMBUG ratingB3-U0-G0Lifetime L90 (hour)>102,000	Color temperature	2700 K CRI 80
Color Deviation3 SDCMBUG ratingB3-U0-G0Lifetime L90 (hour)>102,000	Luminaire efficacy	114 lm/W
BUG rating B3-U0-G0 Lifetime L90 (hour) >102,000	Lamp	32 LED
Lifetime L90 (hour) >102,000	Color Deviation	3 SDCM
	BUG rating	B3-U0-G0
Lifetime L80 (hour) >102,000	Lifetime L90 (hour)	>102,000
	Lifetime L80 (hour)	>102,000

Options

dimensions

Technical information

Mounting	Surface or wall mountable
Housing	Corrosion resistant, marine grade aluminum
	housing
Finishing	Chromate conversion pretreatment followed by
	electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Liquid silicone
Lens / Reflector	PMMA lens with high optical efficiency
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP66
Input voltage	220-240V 50/60Hz
Insulation class	Class I
Weight	7.75 kg
LED module	High power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	10/6 kV
protection	
Power factor	> 0.95
Through wiring	Single power cord entry
Operating	-4050°C
temperature	
Power cord	8" of flexible power cord
Packing box	20*16*100 cm

HEPER USA LLC W227 N546 Westmound Drive Waukesha, 53186 Wisconsin, United States +1 312 910 9740 infoUS@hepergroup.com We reserve the right to change specifications without prior written notice. Edition: 11.05.2024. For current version visit heperlighting.com. All flux (\pm %7 tolerance) and power values (\pm %10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

Project na	me				Туре	Quantit	y
Date		Note					
LW7031.862-EN-T5-700-827							

Light distribution	Rated input power	Color temperature	Control	Product colors
[T5] Type V - 117°	[700] 67 W	[827] 2700 K CRI 80	[ONOFF] On/Off	[HM1] Black
[P4] Pedestrian crosswalk distribution - 20x78°	[350] 34 W	[830] 3000 K CRI 80	[DALI] DALI	[HM2] Dark gray
[T1] Type I - 111x48°	[500] 48 W	[740] 4000 K CRI 70	[AUTO] AutoDIM	[HM3] Anthracite gray
[T2] Type II - 133x48°		[840] 4000 K CRI 80	[STEP] StepDIM	[HM4] Light gray
[T2] Type II - 149x54°				[HM5] White
[T3] Type III - 143x63°				[HM6] Bronze
[T4] Type IV - 117x64°				[CC] (Please specify RAL code)
Extras				
Light output]			
[BS] Backlight Shield				

Consult the factory

[UNI]

120-277V 50/60Hz

Luminaire body options

[DPC]

Double powder coating