

DOMINO W AFX 2 Module

heper t

LW7031.862-US-P4-350-830









[P4] Pedestrian crosswalk distribution

Configuration

Light distribution [P4] 20x78° Delivered lumens flux 4115 lm Rated input power 34 W **Color temperature** 3000 K CRI 80 **Luminaire efficacy** 121 lm/W Lamp 32 LED **Color Deviation** 3 SDCM B1-U0-G1 **BUG** rating Lifetime L90 (hour) >102,000 Lifetime L80 (hour) >102,000

Options

temperature

Technical information

MountingSurface or wall mountableHousingCorrosion resistant, marine grade aluminum
housingFinishingChromate conversion pretreatment followed by
electrostatic powder coatingFastenersStainless steel (AISI 304 / EN 1.4301 grade)

Gasket Liquid silicone
Lens / Reflector PMMA lens with high optical efficiency
Glass / Diffusor Tempered safety glass
Impact protection IK08
Ingress protection IP66
Input voltage 120-277V 50/60Hz

Insulation classClass IWeight17.05 lbsLED moduleHigh power LEDs on metal-core PCBDriverInternal LED driver

Driver surge 10/6 kV

protection
Power factor > 0.95

Through wiring Single power cord entry **Operating** -40...50°C

Power cord 8" of flexible power cord

Notes 3000K CCT or warmer must be selected to be

DarkSky International certified.

Project name		Туре	Quantity		
Date		Note			

LW7031.862-US-P4-350-830-__-_-_-

Light distribution	Rated input power	Color temperature	Control	Product colors	
[P4] Pedestrian crosswalk	[350] 34 W	[830] 3000 K CRI 80	[ONOFF] On/Off	[HM1] Black	
Type - 111x48° Type - 111x48° Type - 133x48° T2] Type - 149x54° T3] Type - 143x63° T4] Type - 117x64° T5] Type - 117° Ty	[500] 48 W [700] 67 W	[827] 2700 K CRI 80 [740] 4000 K CRI 70 [840] 4000 K CRI 80	[0-10V] 0-10V	IHM2] Dark gray [HM3] Anthracite gray [HM4] Light gray [HM5] White [HM6] Bronze [CC] Custom color (Please specify RAL code)	
				specify for code)	

	·	٠.		-	•
Ц	ж	ы	1	a	3

Connectivity

[NM7]

7 Pin NEMA socket

Consult the factory

[MS]

Motion sensor

Luminaire body options

[DPC]

Double powder coating