

DOMINO W AFX 2 Module

heper t

LW7031.862-US-T3-350-827









Type III

Configuration

Light distribution [T3] 143x63° Delivered lumens flux 3785 lm Rated input power 34 W **Color temperature** 2700 K CRI 80 **Luminaire efficacy** 111 lm/W Lamp 32 LED **Color Deviation** 3 SDCM B1-U0-G1 **BUG** rating Lifetime L90 (hour) >102,000 Lifetime L80 (hour) >102,000

Options

temperature

Technical information

MountingSurface or wall mountableHousingCorrosion resistant, marine grade aluminum
housingFinishingChromate conversion pretreatment followed by
electrostatic powder coatingFastenersStainless steel (AISI 304 / EN 1.4301 grade)

GasketLiquid siliconeLens / ReflectorPMMA lens with high optical efficiencyGlass / DiffusorTempered safety glassImpact protectionIK08Ingress protectionIP66Input voltage120-277V 50/60Hz

Insulation classClass IWeight17.05 lbsLED moduleHigh power LEDs on metal-core PCBDriverInternal LED driver

Driver surge

protection

Power factor > 0.95

Through wiring Single power cord entry

Operating -40...50°C

Power cord 8" of flexible power cord
Notes 3000K CCT or warmer must be selected to be
DarkSky International certified.

and applicable standards.

10/6 kV

Project name					Туре	Quantity	
Date		Note					

LW7031.862-US-T3-350-827-__--_--

Light distribution	Rated input power	Color temperature	Control	Product colors
[T3] Type III - 143x63°	[350] 34 W	[827] 2700 K CRI 80	[ONOFF] On/Off	[HM1] Black
[P4] Pedestrian crosswalk distribution - 20x78°	[500] 48 W [700]	[830] 3000 K CRI 80	[0-10V] 0-10V	[HM2] Dark gray
[T1] Type I - 111x48°	67 W	[740] 4000 K CRI 70 [840] 4000 K CRI 80		[HM3] Anthracite gray
[T2] Type II - 133x48°				[HM4] Light gray
[T2] Type II - 149x54°				[HM5] White
[T4] Type IV - 117x64°				[HM6] Bronze
[T5] Type V - 117°				[CC] Custom color (Please specify RAL code)

_			
Essi		-	_
CXI	LT	d	5

Connectivity

[NM7]

7 Pin NEMA socket

Consult the factory

[MS]

Motion sensor

Luminaire body options

[DPC]

Double powder coating