

# **DOMINO W AFX 2 Module**




## LW7031.862-US-T3-500-740





4 23/32"





Type III

### Configuration

Light distribution	[T3] 143x63°
Delivered lumens flux	6315 lm
Rated input power	48 W
Color temperature	4000 K CRI 70
Luminaire efficacy	131 lm/W
Lamp	32 LED
Color Deviation	4 SDCM
BUG rating	B2-U1-G1
Lifetime L90 (hour)	>102,000
Lifetime L80 (hour)	>102,000

#### Options

#### **Technical information**

Mounting	Surface or wall mountable
Housing	Corrosion resistant, marine grade aluminum
	housing
Finishing	Chromate conversion pretreatment followed by
	electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Liquid silicone
Lens / Reflector	PMMA lens with high optical efficiency
Glass / Diffusor	Tempered safety glass
Impact protection	IK08
Ingress protection	IP66
Input voltage	120-277V 50/60Hz
Insulation class	Class I
Weight	17.05 lbs
LED module	High power LEDs on metal-core PCB
Driver	Internal LED driver
Driver surge	10/6 kV
protection	
Power factor	> 0.95
Through wiring	Single power cord entry
Operating	-4050°C
temperature	
Power cord	8" of flexible power cord
Notes	3000K CCT or warmer must be selected to be

3000K CCT or warmer must be selected to be DarkSky International certified.

HEPER USA LLC W227 N546 Westmound Drive Waukesha, 53186 Wisconsin, United States +1 312 910 9740 infoUS@hepergroup.com

We reserve the right to change specifications without prior written notice. Edition: 18.05.2024. For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

Project na	me			Туре	Quantity	
Date		Note				
LW7031.862-US-T3-500-740						

Light distribution	Rated input power	Color temperature	Control	Product colors
<b>[T3]</b> Type III - 143x63°	<b>[500]</b> 48 W	<b>[740]</b> 4000 K CRI 70	[ONOFF] On/Off	[HM1] Black
<b>[P4]</b> Pedestrian crosswalk distribution - 20x78°	[350] 34 W [700]	[827] 2700 K CRI 80 [830]	<b>[0-10V]</b> 0-10V	[HM2] Dark gray
<b>[T1]</b> Type l - 111x48°	67 W	3000 K CRI 80		[HM3] Anthracite gray
<b>[T2]</b> Type II - 133x48°		<b>[840]</b> 4000 K CRI 80		[HM4] Light gray
<b>[T2]</b> Type II - 149x54°				[HM5] White
<b>[T4]</b> Type IV - 117x64°				[HM6] Bronze
<b>[T5]</b> Type V - 117°				[CC] (Please specify RAL code)
Extras		1	1	1

#### Connectivity

[NM7]

7 Pin NEMA socket

## Consult the factory

[MS]

Motion sensor

Luminaire body options

[DPC]

Double powder coating