

DOMINO W AFX 2 Module

heper t

LW7031.862-US-T5-700-830









[T5] Type V

Configuration

Light distribution [T5] 117° Delivered lumens flux 7645 lm Rated input power 67 W **Color temperature** 3000 K CRI 80 **Luminaire efficacy** 114 lm/W Lamp 32 LED **Color Deviation** 3 SDCM B3-U0-G0 **BUG** rating Lifetime L90 (hour) >102,000 Lifetime L80 (hour) >102,000

Options

Technical information

MountingSurface or wall mountableHousingCorrosion resistant, marine grade aluminum
housingFinishingChromate conversion pretreatment followed by
electrostatic powder coatingFastenersStainless steel (AISI 304 / EN 1.4301 grade)

GasketLiquid siliconeLens / ReflectorPMMA lens with high optical efficiencyGlass / DiffusorTempered safety glassImpact protectionIK08Ingress protectionIP66Input voltage120-277V 50/60Hz

Insulation classClass IWeight17.05 lbsLED moduleHigh power LEDs on metal-core PCBDriverInternal LED driver

Driver surge

and applicable standards.

temperature

protection
Power factor > 0.95
Through wiring Single power cord entry
Operating -40...50°C

Power cord 8" of flexible power cord

Notes 3000K CCT or warmer must be selected to be

DarkSky International certified.

10/6 kV

| Project name | | | | Туре | Quantity | |
|--------------|--|------|--|------|----------|--|
| Date | | Note | | | | |

LW7031.862-US-T5-700-830-__--__-

| Light distribution | Rated input power | Color temperature | Control | Product colors |
|--|------------------------|--|-------------------------|---|
| [T5] Type V - 117° | [700] 67 W | [830] 3000 K CRI 80 | [ONOFF] On/Off | [HM1] Black |
| [P4] Pedestrian crosswalk distribution - 20x78° | [350] 34 W | [827] 2700 K CRI 80 | [0-10V] 0-10V | [HM2] Dark gray |
| [T1] Type I - 111x48° | [500] 48 W | [740] 4000 K CRI 70 [840] 4000 K CRI 80 | | [HM3] Anthracite gray |
| [T2] Type II - 133x48° | | | | [HM4] Light gray |
| [T2] Type II - 149x54° | | | | [HM5] White |
| [T3] Type III - 143x63° | | | | [HM6] Bronze |
| [T4] Type IV - 117x64° | | | | [CC] Custom color (Please specify RAL code) |

| Extr | as |
|------|----|
|------|----|

Connectivity

[NM7]

7 Pin NEMA socket

Consult the factory

[MS]

Motion sensor

Luminaire body options

[DPC]

Double powder coating