

# PRIFMA W AFX 2 Module



IK08 IP66



LW2042.862-EN-T5-700-840-EN-C1





## Variant

|                        |               |
|------------------------|---------------|
| Light distribution     | [T5] 117°     |
| Delivered lumens flux  | 7645 lm       |
| Rated input power      | 67 W          |
| Colour temperature     | 4000 K CRI 80 |
| Luminaire efficacy     | 114 lm/W      |
| Lamp                   | 32 LED        |
| MacAdam Ellipse        | 4 SDCM        |
| BUG rating             | B3-U0-G0      |
| Lifetime L90B50 (hour) | >102,000      |
| Lifetime L80B50 (hour) | >102,000      |

## Options

## Technical information

|                         |                                                                           |
|-------------------------|---------------------------------------------------------------------------|
| Mounting                | Wall mountable                                                            |
| Housing                 | Corrosion resistant, marine grade aluminum housing                        |
| Finishing               | Chromate conversion pretreatment followed by electrostatic powder coating |
| Fasteners               | Stainless steel (AISI 304 / EN 1.4301 grade)                              |
| Gasket                  | Liquid silicone                                                           |
| Lens / Reflector        | PMMA lens with high optical efficiency                                    |
| Glass / Diffusor        | Tempered safety glass                                                     |
| Impact protection       | IK08                                                                      |
| Ingress protection      | IP66                                                                      |
| Input voltage           | 220-240V 50/60Hz                                                          |
| Insulation class        | Class I                                                                   |
| Weight                  | 5.3 kg                                                                    |
| LED module              | High power LEDs on metal-core PCB                                         |
| Driver                  | Internal LED driver                                                       |
| Driver surge protection | 6/4 kV                                                                    |
| Power factor            | > 0.98                                                                    |
| Through wiring          | Single cable entry                                                        |
| Operating temperature   | -40...50°C                                                                |
| Cable                   | 0.5 m of flexible cable                                                   |
| Packing box dimensions  | 19*8*62 cm                                                                |



[T5]

Type V, Symmetric

### HPR Pazarlama A.Ş.

Başkent OSB 22. Cd. No: 2, Malıköy, Temelli,  
Sincan, 06909 Ankara, Turkey  
+90 312 267 54 30  
info@hepergroup.com

### HEPER Europe GmbH

Ahornweg 5a, 58675  
Hemer, Germany  
+49 237 2901 2975  
infoEU@hepergroup.com

We reserve the right to change specifications without prior written notice. Edition: 27.04.2024.  
For current version visit [heperlighting.com](http://heperlighting.com). All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

|                                                      |  |             |  |                 |  |
|------------------------------------------------------|--|-------------|--|-----------------|--|
| <b>Project name</b>                                  |  | <b>Type</b> |  | <b>Quantity</b> |  |
| <b>Date</b>                                          |  | <b>Note</b> |  |                 |  |
| <b>LW2042.862-EN-T5-700-840-__-EN-C1-__-__-__-__</b> |  |             |  |                 |  |

| Light distribution                                                              | Rated input power    | Colour temperature            | Control                  | Product colours                                        |
|---------------------------------------------------------------------------------|----------------------|-------------------------------|--------------------------|--------------------------------------------------------|
| <b>[T5]</b><br>Type V, Symmetric - 117°                                         | <b>[700]</b><br>67 W | <b>[840]</b><br>4000 K CRI 80 | <b>[ONOFF]</b><br>On/Off | <b>[HM1]</b><br>Black                                  |
| <b>[P4]</b><br>Special pedestrian road distribution-right side traffic - 20x78° | <b>[350]</b><br>34 W | <b>[827]</b><br>2700 K CRI 80 | <b>[DALI]</b><br>DALI    | <b>[HM2]</b><br>Dark grey                              |
| <b>[T1]</b><br>Type I, Asymmetric, Side throw - 111x48°                         | <b>[500]</b><br>48 W | <b>[830]</b><br>3000 K CRI 80 |                          | <b>[HM3]</b><br>Anthracite grey                        |
| <b>[T2]</b><br>Type II, Asymmetric, Side throw - 133x48°                        |                      | <b>[740]</b><br>4000 K CRI 70 |                          | <b>[HM4]</b><br>Light grey                             |
| <b>[T2]</b><br>Type II, Asymmetric, Side throw - 149x54°                        |                      |                               |                          | <b>[HM5]</b><br>White                                  |
| <b>[T3]</b><br>Type III, Asymmetric, Side throw - 143x63°                       |                      |                               |                          | <b>[HM6]</b><br>Bronze                                 |
| <b>[T4]</b><br>Type IV, Asymmetric, Forward throw - 117x64°                     |                      |                               |                          | <b>[CC]</b><br>Custom colour (Please specify RAL code) |
| <b>Extras</b>                                                                   |                      |                               |                          |                                                        |
| <b>Light output</b>                                                             |                      |                               |                          |                                                        |
| <b>[BS]</b><br>Backlight Shield                                                 |                      |                               |                          |                                                        |
| <b>[CLO]</b><br>Constant light output                                           |                      |                               |                          |                                                        |
| <b>Consult the factory</b>                                                      |                      |                               |                          |                                                        |
| <b>[UNI]</b><br>120-277V 50/60Hz                                                |                      |                               |                          |                                                        |
| <b>Luminaire body options</b>                                                   |                      |                               |                          |                                                        |
| <b>[DPC]</b><br>Double powder coating                                           |                      |                               |                          |                                                        |