

HANDRA Forward - Ø48 mm



IK10 IP65





LH5004.595-EN-SLFH-350-740-CC-3V-350-C3



22 mm
55/64"



40 mm
1 37/64"



[SLFH]

Special linear,
Forward throw

Variant

Light distribution	[SLFH] 44x46°
Delivered lumens flux	100 lm
Rated input power	1 W
Colour temperature	4000 K CRI 70
Luminaire efficacy	100 lm/W
Lamp	1 LED
MacAdam Ellipse	4 SDCM
Lifetime L90B50 (hour)	>102,000
Lifetime L80B50 (hour)	>102,000

Options

Technical information

Housing	Corrosion resistant, die-cast, marine grade aluminum housing
Finishing	Chromate conversion pretreatment followed by electrostatic powder coating
Fasteners	Stainless steel (AISI 304 / EN 1.4301 grade)
Gasket	Liquid gasket
Lens / Reflector	High reflectance aluminium coating
Glass / Diffusor	Custom Design PMMA Diffusor
Impact protection	IK10
Ingress protection	IP65
Input voltage	3 Vdc (Max) 350 mA
Insulation class	Class III
Weight	0.05 kg
LED module	High power LEDs on metal-core PCB
Driver	External LED driver
Through wiring	Single cable entry
Operating temperature	-25...50°C
Cable	0.2 m of flexible cable
Packing box dimensions	7*7*7 cm
Notes	QUICK SHIP: Some variants will be delivered faster. Please consult the factory.

HPR Pazarlama A.Ş.
Başkent OSB 22. Cd. No: 2, Malıköy, Temelli,
Sincan, 06909 Ankara, Turkey
+90 312 267 54 30
info@hepergroup.com

HEPER Europe GmbH
Ahornweg 5a, 58675
Hemer, Germany
+49 237 2901 2975
infoEU@hepergroup.com

We reserve the right to change specifications without prior written notice. Edition: 17.05.2024.
For current version visit heperlighting.com. All flux (±%7 tolerance) and power values (±%10 tolerance) are derived following appropriate IES, CIE, and applicable standards.

Accessories (To be ordered separately)


Mounting accessories



**DALI & On/Off
driver within an
IP67 box for 1 to 6
HANDRA modules**

007502063


Mounting accessories



**DALI & On/Off
driver within an
IP67 box for 7 to
15 HANDRA
modules**

007502064








Mounting accessories



**DALI & On/Off
driver within an
IP67 box for 16 to
35 HANDRA
modules**

007502065

Project name		Type		Quantity	
Date		Note			
LH5004.595-EN-SLFH-350-740-__-CC-3V-350-C3-__					

Light distribution	Rated input power	Colour temperature	Control	Product colours
[SLFH] Special linear, Forward throw - 44x46°	[350] 1 W	[740] 4000 K CRI 70	[ONOFF] On/Off	[HM1] Black 
		[827] 2700 K CRI 80	[DALI] DALI	[HM2] Dark grey 
		[830] 3000 K CRI 80		[HM3] Anthracite grey 
		[840] 4000 K CRI 80		[HM4] Light grey 
				[HM5] White 
				[HM6] Bronze 
				[CC]  Custom colour (Please specify RAL code)

Accessories (*To be ordered separately*)

Mounting accessories

[007502063]
DALI & On/Off driver
within an IP67 box for
1 to 6 HANDRA
modules

[007502064]
DALI & On/Off driver
within an IP67 box for
7 to 15 HANDRA
modules

[007502065]
DALI & On/Off driver
within an IP67 box for
16 to 35 HANDRA
modules